

**E.2**

**CAP SETTLEMENT RAD AND OUTBOARD**

# GEOSYNTEC CONSULTANTS

## COMPUTATION COVER SHEET

**Client:** Honeywell **Project:** Onondaga Lake ILWD IDS **Project/Proposal #:** GJ4741 **Task #:** 1

### TITLE OF COMPUTATIONS

### CAP-INDUCED SETTLEMENT EVALUATION FOR REMEDATION AREA D AND THE ADDENDUM

COMPUTATIONS BY:

Signature

*Fan Zhu*

1/13/2011

DATE

Printed Name

Fan Zhu

and Title

Senior Staff Engineer

ASSUMPTIONS AND PROCEDURES  
CHECKED BY:

(Peer Reviewer)

Signature

*R. Kulasingam / Ming Zhu*

01/13/2011

DATE

Printed Name

R. Kulasingam/Ming Zhu

and Title

Senior Engineer/Project  
Engineer

COMPUTATIONS CHECKED BY:

Signature

*Joseph Sura*

Jan. 13, 2011

DATE

Printed Name

Joseph Sura

and Title

Senior Staff Engineer

COMPUTATIONS

BACKCHECKED BY:

(Originator)

Signature

*Fan Zhu*

1/13/2011

DATE

Printed Name

Fan Zhu

and Title

Senior Staff Engineer

APPROVED BY:

(PM or Designate)

Signature

*J. Beech*

01/13/2011

DATE

Printed Name

Jay Beech

and Title

Principal

APPROVAL NOTES:

REVISIONS (Number and initial all revisions)

NO.	SHEET	DATE	BY	CHECKED BY	APPROVAL
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

*Prepared for*

**Parsons**

301 Plainfield Road, Suite 350

Syracuse, New York 13212

# **CAP-INDUCED SETTLEMENT EVALUATION FOR REMEDIATION AREA D**

**ONONDAGA LAKE  
SYRACUSE, NEW YORK**

*Prepared by*

**Geosyntec**   
consultants

engineers | scientists | innovators

1255 Roberts Boulevard, Suite 200

Kennesaw, Georgia 30144

Project Number: GJ4741

January 2011

## TABLE OF CONTENTS

1.	INTRODUCTION .....	1
2.	SUBSURFACE CONDITIONS .....	1
3.	MATERIAL PROPERTIES .....	2
4.	SETTLEMENT ANALYSIS .....	6
4.1	Methodology .....	6
4.2	Dredge Cut Depths and Cap Thicknesses Considered .....	10
4.3	Settlement Calculations .....	11
4.4	Cumulative Upward Consolidation Water Flow .....	12
5.	CONCLUSIONS .....	15
	REFERENCES .....	16

## LIST OF TABLES

Table 1.	$C_{ce}$ and $C_{re}$ from Oedometer Tests for SOLW
Table 2.	$C_{ce}$ and $C_{re}$ from Oedometer Tests for Marl
Table 3.	$C_{ce}$ and $C_{re}$ from Oedometer Tests for Silt and Clay in SMU 1
Table 4.	$C_{ce}$ and $C_{re}$ from Oedometer Tests for Silt and Clay in SMU 2
Table 5.	Summary of the Material Properties used in Analysis
Table 6.	Selected Reasonable Upper and Lower Bound Values for Consolidation Parameters

## LIST OF FIGURES

Figure 1.	Remediation Area D
Figure 2.	Areas and Subsurface Layer Thicknesses
Figure 3.	Comparison of Results from Conventional Oedometer Tests and SIC Tests

## **TABLE OF CONTENTS (Continued)**

- Figure 4. Interpretation of Modified Secondary Compression Index for SOLW
- Figure 5. Interpretation of Modified Secondary Compression Index for Marl
- Figure 6. Interpretation of Modified Secondary Compression Index for Silt and Clay in SMU 1
- Figure 7. Interpretation of Modified Secondary Compression Index for Silt and Clay in SMU 2
- Figure 8. Interpretation of Coefficient of Consolidation Index for SOLW
- Figure 9. Interpretation of Coefficient of Consolidation Index for Marl
- Figure 10. Interpretation of Coefficient of Consolidation Index for Silt and Clay in SMU 1
- Figure 11. Interpretation of Coefficient of Consolidation Index for Silt and Clay in SMU 2
- Figure 12. Finite difference method based numerical solution for the 1-D consolidation equation
- Figure 13. Settlement Analysis Results for Areas 1 to 12 for 30-Year Period
- Figure 14. Settlement Analysis Results for Area 3 for 2-Year Period
- Figure 15. Calculated Cumulative Consolidation Water Flow

## **LIST OF ATTACHMENTS**

- Attachment A. Subsurface Layer Thickness Contours
- Attachment B. Conventional Oedometer Test Results Summary
- Attachment C. Examples of Calculations
- Attachment D. Calculated Excess Pore Water Pressure Isochrones

## **1. INTRODUCTION**

This report presents calculations of the amount and rate of consolidation settlement anticipated after dredging and placement of a subaqueous cap in Remediation Area D of the Onondaga Lake Bottom Site. Specifically, this report presents: (i) the total settlement (including primary settlement and secondary settlement) at the end of 30 years after placement of the cap and at the end of two years for the area with the highest estimated settlement; and (ii) the upward flow rate of consolidation water.

Remediation Area D, which is also referred to as the In-Lake Waste Deposit (ILWD), is shown in Figure 1. Remediation Area D consists predominantly of Sediment Management Unit (SMU) 1 with limited portions of SMUs 2 and 7. The dredging plan and the maximum and minimum cap thicknesses in Remediation Area D are documented in the main text of the Capping, Dredging, and Habitat Design Report.

The remainder of this report presents: (i) subsurface conditions; (ii) material properties; (iii) settlement analysis; and (iv) conclusions.

## **2. SUBSURFACE CONDITIONS**

Extensive pre-design investigations (PDIs) were conducted in the ILWD from 2005 to 2007 to characterize the subsurface conditions. Detailed information regarding the subsurface stratigraphy is presented in a calculation package titled “*Summary of Subsurface Stratigraphy and Material Properties*” (referred to as the ILWD Data Package) for the Stability Evaluation of the ILWD [appendix of the Capping, Dredging, and Habitat Design Report]. In summary, the subsurface stratigraphy primarily consists of the following materials: Solvay waste (SOLW), Marl, Silt and Clay, Silt and Sand, Sand and Gravel, Till, and Shale. In isolated areas of the ILWD, thin silt layers are present over the SOLW.

The subsurface profile of the ILWD was developed based on the elevations of each layer from the boring logs. As explained in the ILWD Data Package, elevations for the deeper surfaces (e.g., bottom of Silt and Clay, bottom of Silt and Sand) that are below the depth of the shallow borings were estimated based on a limited number of deeper borings in the ILWD area. The deeper layers (i.e., Silt and Sand, Sand and Gravel, Till, and Shale) were considered as incompressible layers in the settlement analysis.

For the purpose of the settlement analysis presented herein, Remediation Area D was divided into 12 areas based on the thickness of the SOLW, Marl, and Silt and Clay layers. Representative values of SOLW, Marl, and Silt and Clay thicknesses were selected for settlement analysis in each area. The thin isolated silt layers were assumed to be part of the SOLW because their impact on settlement is expected to be insignificant. The divided areas and selected layer thicknesses for the settlement analyses are presented in Figure 2. The subsurface layer thickness contours are presented in Attachment A of this report. It is noted that the selected subsurface thickness values represent a general estimation of the average thickness of each layer in a particular area. The actual subsurface layer thickness at any point within an area may be higher or lower than the selected value.

### **3. MATERIAL PROPERTIES**

The material properties required for settlement analysis include: (i) unit weight of cap and subsurface materials (i.e., SOLW, Marl, and Silt and Clay); and (ii) consolidation parameters of subsurface materials. For the calculation of upward flow rate of consolidation water, the hydraulic conductivities of the subsurface materials were also needed.

#### Unit Weight

The unit weight of Cap material was assumed to be 120 pcf in the analysis. The unit weight of SOLW, Marl, and Silt and Clay were assumed to be 81 pcf, 98 pcf and 108 pcf, respectively, as presented in the ILWD Data Package.

#### Consolidation Parameters

The consolidation parameters needed for settlement analysis are: modified compression index ( $C_{ce}$ ), modified recompression index ( $C_{re}$ ), modified secondary compression index ( $C_{ae}$ ), and coefficient of consolidation ( $c_v$ ). These parameters were interpreted from consolidation test data.

Two types of consolidation tests were performed, as follows:

- (i) Conventional oedometer test: The conventional oedometer test data can be used to determine all the consolidation parameters needed for settlement

analyses. Tests were performed on samples of SOLW, Marl, and Silt and Clay. The test reports are included in Attachment B of this report.

- (ii) Seepage-induced consolidation (SIC) test: The SIC tests were completed in general accordance with the method presented by Znidarcic, et al. (1992). The test is run on a disturbed sample that has been slurried. A load is then applied by creating a constant flow rate in the sample. Load is then increased to the maximum desired level after constant flow is reached. The change in void ratio and permeability is measured as the loads are applied. Only the compression index can be calculated based on SIC test data. For Remediation Area D, SIC tests were performed primarily on samples of SOLW. The test results are presented in Phase I and Phase II Pre-Design Investigation Data Summary Report [Parsons 2007 and 2009].

As indicated previously, both tests were performed on samples of SOLW. The rationale for interpreting the  $C_{ce}$  value of SOLW from only the conventional oedometer test results is as follows:

- (i) consolidation curves from conventional oedometer tests indicate an “apparent” pre-consolidation pressure between 1,000 to 3,000 psf, as shown by the solid lines in Figure 3. The slope of the consolidation curve is flatter when the vertical effective stress is less than the “apparent” pre-consolidation pressure as compared to when the vertical effective stress is greater than the “apparent” pre-consolidation pressure. It indicates that the compressibility of SOLW under a small stress condition (i.e., less than 1,000 psf) is less than the compressibility under a higher stress condition (i.e., greater than 1,000 psf). As presented in the ILWD Data Package, the consolidated undrained triaxial tests performed for SOLW during the PDI showed higher undrained shear strength ratios under a small stress condition (i.e., less than 1,000 psf) than under higher stress conditions (i.e., greater than 1,000 psf). This is likely due to the overconsolidated condition of the samples in the lab from the presence of an “apparent” pre-consolidation pressure;
- (ii) SIC tests were performed on disturbed samples, and as expected, did not indicate any “apparent” pre-consolidation pressure, as indicated by the dashed lines in Figure 3. It is believed that the disturbance of the sample in the SIC



tests changed the structure of the sample, and therefore, the SIC tests did not show the “apparent” pre-consolidation pressure; and

- (iii) the vertical effective stress of SOLW in the field before and after capping is less than the “apparent” pre-consolidation pressure. Therefore, the  $C_{ce}$  value of SOLW should be interpreted from the conventional oedometer test, using the portion of the consolidation curve corresponding to the potential stress condition of SOLW in the field before and after capping (i.e., from 100 to 1,000 psf).

The values interpreted from oedometer tests for  $C_{ce}$  and  $C_{re}$  of SOLW, Marl, and Silt and Clay are presented in Tables 1 through 4. The mean values of  $C_{ce}$  and  $C_{re}$  were used for the settlement analysis in all areas. The interpretation of  $C_{ae}$  and  $c_v$  for SOLW, Marl, and Silt and Clay are presented in Figures 4 through 11. The representative values were used for the settlement analysis.

For sensitivity analyses to evaluate the impact of consolidation parameter uncertainty on calculated settlement, reasonable upper and lower bound values were selected for  $C_{ce}$ ,  $C_{re}$ ,  $C_{ae}$ , and  $c_v$ . For  $C_{ce}$  and  $C_{re}$ , the reasonable upper bound values were selected as the smaller of the calculated “mean plus standard deviation” and the maximum value, and the reasonable lower bound values were selected as the larger of the calculated “mean minus standard deviation” and the minimum value (see Tables 1 through 4). For  $C_{ae}$  and  $c_v$ , reasonable upper and lower bound values were selected based on the variability within the stress range of interest (see Figures 4 through 11).

As presented in the ILWD Data Package, comparison of calculated in-situ vertical effective stresses and the “apparent” pre-consolidation pressures interpreted from oedometer tests indicates that Marl has an OCR of about 1.2, and Silt and Clay is normally consolidated. The analyses presented herein assumed that both Marl and Silt and Clay are normally consolidated. This assumption will lead to slightly higher total settlement estimates.

### Hydraulic Conductivity

According to the calculation package titled “*Summary of Subsurface Stratigraphy and Material Properties*” (referred to as the West Wall Data Package) for the Onondaga Lake West Wall Final Design [Geosyntec 2009], the measured hydraulic conductivity of SOLW varies from  $4.95 \times 10^{-6}$  cm/s to  $2.78 \times 10^{-5}$  cm/s. The measured hydraulic conductivity of Silt and Clay varies from  $4.9 \times 10^{-8}$  cm/s to  $4.41 \times 10^{-7}$  cm/s. These values are based on hydraulic conductivity tests performed on samples of SOLW and Silt and Clay from the Wastebed B/Harbor Book (WB-B/HB) area. For the purposes of analysis presented herein, the hydraulic conductivities of SOLW and Silt and Clay were assumed as  $1 \times 10^{-5}$  cm/s and  $1 \times 10^{-7}$  cm/s, respectively. These values are also reasonably consistent (i.e., same order of magnitude) as the values being used in the groundwater upwelling evaluations for the ILWD. The hydraulic conductivity of Marl was assumed the same as for Silt and Clay. Hydraulic conductivities were only used for the calculation of excess pore water pressures at layer interfaces as part of the upward flow of consolidation water calculations. Hydraulic conductivity values ranging from  $1 \times 10^{-7}$  cm/sec to  $5 \times 10^{-5}$  cm/sec have minimum impact on the calculated amount of consolidation water because the hydraulic conductivities only affect the calculation of pore water pressure at the interface between soil layers (refer to Equation 11B presented below). The coefficient of consolidation  $c_v$  has significant impact on the calculated amount of consolidation water flow at any given time. The  $c_v$  is related to the hydraulic conductivity and compressibility, but was calculated directly based on consolidation tests on ILWD samples.

A summary of the material properties used in the analyses is provided in Table 5. The reasonable upper and lower bound consolidation parameters used in the sensitivity analysis are summarized in Table 6.

## 4. SETTLEMENT ANALYSIS

### 4.1 Methodology

#### Consolidation Settlement

Settlement of the SOLW, Marl, and Silt and Clay was calculated using equations for conventional one-dimensional (1-D) consolidation theory used in geotechnical engineering [Holtz and Kovacs, 1981]. Settlement is caused by the following mechanisms:

- primary compression of the SOLW, Marl, and Silt and Clay due to overburden loading imposed by the cap; and
- secondary compression resulting from the plastic realignment of the fabric (i.e., creep) of SOLW, Marl, and Silt and Clay under the sustained loading.

The general forms of the settlement equations are given below:

#### Primary Settlement

$$S_p = C_{r\varepsilon} H \log \left( \frac{\sigma'_{vo} + \Delta \sigma'_v}{\sigma'_{vo}} \right) \text{ for } \sigma'_{vo} + \Delta \sigma'_v \leq \sigma'_p \quad (1)$$

$$S_p = C_{r\varepsilon} H \log \left( \frac{\sigma'_p}{\sigma'_{vo}} \right) + C_{c\varepsilon} H \log \left( \frac{\sigma'_{vo} + \Delta \sigma'_v}{\sigma'_p} \right) \text{ for } \sigma'_{vo} \leq \sigma'_p \text{ and } \sigma'_{vo} + \Delta \sigma'_v > \sigma'_p \quad (2A)$$

$$S_p = C_{c\varepsilon} H \log \left( \frac{\sigma'_{vo} + \Delta \sigma'_v}{\sigma'_{vo}} \right) \text{ for } \sigma'_{vo} \geq \sigma'_p \quad (2B)$$

#### Secondary Settlement

$$S_s = C_{a\varepsilon} H \log \left( \frac{t_2}{t_1} \right) \quad (3)$$

#### Total Settlement

$$S = S_p + S_s \quad (4)$$

Where,

- $S_p$  = primary settlement;
- $S_s$  = secondary settlement;
- $S$  = total settlement;
- $C_{c\varepsilon}$  = modified compression index;
- $C_{r\varepsilon}$  = modified recompression index;
- $C_{\alpha\varepsilon}$  = modified secondary compression index;
- $H$  = initial thickness of compressible layer;
- $\sigma'_{vo}$  = initial effective overburden stress;
- $\sigma'_p$  = preconsolidation pressure;
- $\Delta \sigma'_v$  = increase in effective stress due to the loading;
- $t_1$  = time for completion of primary compression; and
- $t_2$  = time when settlement due to secondary compression is computed (i.e., unless stated otherwise, assumed to be 30 years for this analysis).

The following equations related to the time rate of consolidation were used to calculate  $t_1$ :

$$T = \frac{c_v t}{H_{dr}^2} \quad (5)$$

$$T = \frac{\pi}{4} \left( \frac{U\%}{100} \right)^2 \text{ for } U < 60\% \quad (6A)$$

$$T = 1.781 - 0.933 \log(100 - U\%) \text{ for } U > 60\% \quad (6B)$$

The completion of primary compression was considered as  $U = 90\%$ , in accordance with common engineering practice. Based on Equation 6B,  $T = 0.848$  when  $U = 90\%$ . Therefore,  $t_1$  can be calculated using the following equation:

$$t_1 = 0.848 \frac{H_{dr}^2}{c_v} \quad (7)$$

Where,

$T$  = time factor;  
 $c_v$  = coefficient of consolidation;  
 $H_{dr}$  = longest drainage path; and  
 $U$  = average degree of consolidation.

#### Upward Flow of Consolidation Water

Cumulative upward flow volume of consolidation water from SOLW, Marl, and Silt and Clay at any time can be calculated as follows for use in cap design:

$$V_t = \sum \left( \left( \frac{P_i \%}{100} \right) \left( \frac{U_{i,t} \%}{100} \right) S_{pi} + \left( \frac{P_i \%}{100} \right) S_{si,t} \right) \quad (8)$$

Where,

$V_t$  = cumulative upward flow volume of consolidation water at time  $t$ ;  
 $P_i$  = percentage of thickness of layer  $i$  contributing to upward flow of consolidation water;  
 $U_{i,t}$  = average degree of consolidation for layer  $i$  at time  $t$ ;  
 $S_{pi}$  = ultimate primary settlement of layer  $i$ ; and  
 $S_{si,t}$  = secondary settlement of layer  $i$  at time  $t$ . For simplicity of calculation, secondary settlement was assumed to start when  $U = 93\%$  ( $T \approx 1$ ), even though in the settlement calculation presented above,  $U=90\%$  was considered as the completion of primary settlement

Both  $P$  and  $U$  can be calculated from contours of excess pore water pressure variation with depth for different times (i.e., isochrones). Simpson's rule is used to calculate relative areas from contours of excess pore water pressure, which are used to estimate  $U$  at different times. The following governing equation for one-dimensional consolidation can be solved using the finite difference method (FDM) to develop isochrones.

$$\frac{\partial u}{\partial t} = \frac{k}{\gamma_w m_v} \frac{\partial^2 u}{\partial z^2} = c_v \frac{\partial^2 u}{\partial z^2} \quad (9)$$

Where,

- $u$  = excess pore water pressure;
- $t$  = time;
- $k$  = hydraulic conductivity;
- $\gamma_w$  = unit weight of water; and
- $m_v$  = coefficient of volume change.

The FDM solution is expressed in terms of the following dimensionless (relative) parameters:

$$\bar{u} = \frac{u}{u_R} \quad (10A)$$

$$\bar{t} = \frac{t}{t_R} \quad (10B)$$

$$\bar{z} = \frac{z}{z_R} \quad (10C)$$

Where,

- $\bar{u}$  = dimensionless (relative) excess pore water pressure;
- $u_R$  = maximum excess pore water pressure induced by the loading;
- $\bar{t}$  = dimensionless (relative) time;
- $t_R$  = time for 93% consolidation, calculated as  $t_R = \frac{z_R^2}{c_v}$  ;
- $\bar{z}$  = relative depth; and
- $z_R$  = maximum depth of all layers modeled.

The finite difference nodes are presented in Figure 12. The FDM equations for a node in a homogeneous layer and at a layer interface are presented in Equations 11A and 11B, respectively.

$$\bar{u}_{0,\bar{t}+\Delta\bar{t}} = \frac{\Delta\bar{t}}{(\Delta\bar{z})^2} (\bar{u}_{1,\bar{t}} + \bar{u}_{3,\bar{t}} - 2\bar{u}_{0,\bar{t}}) + \bar{u}_{0,\bar{t}} \quad (11A)$$

$$\bar{u}_{0,\tilde{t}+\Delta\tilde{t}} = A \frac{\Delta\tilde{t}}{(\Delta\tilde{z})^2} \left( B\bar{u}_{1,\tilde{t}} + C\bar{u}_{3,\tilde{t}} - 2\bar{u}_{0,\tilde{t}} \right) + \bar{u}_{0,\tilde{t}} \quad (11B)$$

The parameters referred to as A, B, and C can be calculated using the following equations (where  $k_1$  and  $k_2$  are hydraulic conductivities of the top and bottom layers, respectively, and  $c_{v1}$  and  $c_{v2}$  are coefficients of consolidation of the top and bottom layers, respectively):

$$A = \frac{1 + \frac{k_2}{k_1}}{1 + \left( \frac{k_2}{k_1} \right) \left( \frac{c_{v1}}{c_{v2}} \right)} \quad (12A)$$

$$B = \frac{2k_1}{k_1 + k_2} \quad (12B)$$

$$C = \frac{2k_2}{k_1 + k_2} \quad (12C)$$

For numerical stability of the FDM implementation, the following should be satisfied:

$$\frac{\Delta\tilde{t}}{(\Delta\tilde{z})^2} < 0.5 \quad (13)$$

#### **4.2 Dredge Cut Depths and Cap Thicknesses Considered**

As documented in the main text of the Capping, Dredging, and Habitat Design Report, the proposed dredging depth in Remediation Area D, excluding hot spot removal, is between 0 m and 3 m (or 10 ft). The proposed cap has a thickness of approximately 3 to 4.5 ft assuming average overplacement and a maximum thickness of 5.5 ft for maximum overplacement. In the settlement analysis performed herein,

dredging depths of 0 ft, 3 ft, 6 ft, and 10 ft, and cap thicknesses of 3 ft, 4 ft, and 5.5 ft were considered for each of the 12 areas identified in Figure 2.

### **4.3 Settlement Calculations**

#### **Settlement Analysis**

Cap-induced settlement analyses were performed for each of the 12 areas for all combinations of the considered dredging depths and cap thicknesses. The calculated settlement includes the primary settlement and secondary settlement that will occur within 30 years of cap placement. The following assumptions were made for the purposes of the analyses presented herein:

- Both Marl and Silt and Clay were considered as one layer in the consolidation rate calculation (i.e., the average degree of consolidation at the end of 30 years and the time needed to reach 90% primary consolidation) because their  $c_v$  values are comparable. The  $c_v$  value of Silt and Clay was applied to this combined layer due to the relatively larger thickness of Silt and Clay compared to Marl.
- The SOLW layer was considered to be a singly drained layer. The combined Marl and Silt and Clay layer was assumed to be a doubly drained layer. The  $c_v$  value of SOLW is much larger than that for the combined layer and, therefore, the excess pore water pressure in the SOLW dissipates (in the upward direction) much faster than the excess pore water pressure in the combined layer. The combined layer behaves similar to a doubly drained layer after most of the excess pore water pressure in the SOLW has dissipated. This assumption will be validated in Section 4.4.
- Secondary compression starts when 90% of the primary consolidation is reached.

The settlement calculations were performed using EXCEL<sup>®</sup> spreadsheets. An example calculation is shown in Attachment C. Analysis results are presented in Figure 13. For each area, the cap-induced settlement can be read or interpolated from the charts for a given proposed dredging depth and cap thickness that is within the range of the values evaluated.



An additional cap-induced settlement analysis was performed to evaluate the settlement that will occur within two years after cap placement. Area 3 was selected for this analysis because it is the area with the largest calculated settlement for the different combinations of dredging depth and cap thickness. The settlement analysis results for Area 3 for a 2-year period are presented in Figure 14.

#### Sensitivity Analysis

Sensitivity analyses were performed to evaluate the impact of variability in consolidation parameters on the calculated settlement. Analyses were performed for the condition with a 2-m (6.6 ft) dredge and 4-ft cap thickness, which represents the average dredge depth and cap thickness for Remediation Area D. The reasonable upper and lower bound values presented in Table 6 were used to calculate the potential upper bound and lower bound settlement magnitude. In the calculation of potential upper bound of settlement magnitude, Marl and Silt and Clay were considered as one layer in the consolidation rate calculation and the  $c_v$  value of Silt and Clay was applied to this layer. In the calculation of potential lower bound of settlement magnitude, all of the SOLW, Marl, and Silt and Clay were assumed as one doubly drained layer for the consolidation rate calculation because the reasonable lower bound  $c_v$  values of the three materials are comparable. The  $c_v$  value of Silt and Clay was applied to this combined layer.

Based on settlement calculations presented in Figure 13 for a 2-m dredge and 4-ft cap thickness condition, the settlement ranges from 0.5 ft to 0.7 ft. The sensitivity analysis results indicated that the settlement in Remediation Area D may range from 0.2 ft to 1.0 ft for a 2-m dredge and 4-ft cap thickness condition.

#### **4.4 Cumulative Upward Consolidation Water Flow**

After cap placement, water stored in the voids of the subsurface soil will be squeezed out due to the consolidation of the subsurface soil. Part of the water will flow upward. For the purpose of the analyses presented herein, the upward flow rate of consolidation water was evaluated for the condition with a 2-m (6.6 ft) dredge and 4-ft cap thickness, which represents the average dredge depth and cap thickness for Remediation Area D. These analyses were performed using average/representative parameters. The following assumption was made for this analysis:

- Since Marl and Silt and Clay have comparable  $c_v$  values, they were modeled as one layer. The  $c_v$  value of Silt and Clay was applied to this combined layer. The SOLW layer was modeled separately because its  $c_v$  value is much higher than the value for the Marl and Silt and Clay.

Based on this assumption, the analysis of upward flow rate of consolidation water was performed as follows:

- (i) calculate the variation of excess pore water pressure with depth and time, according to the subsurface conditions and material properties; and plot the isochrones of excess pore water pressure;
- (ii) based on calculated excess pore water pressures, determine the average degree of consolidation (U) of SOLW and the combined layer at different times;
- (iii) based on calculated excess pore water pressures, determine the percentage of consolidation water flowing upward (P) for the SOLW and the combined layer (results indicated P is 100% for SOLW and 50% for the combined layer);
- (iv) calculate the ultimate primary settlement of SOLW and upper half of the combined layer; and
- (v) calculate the primary and secondary settlement of SOLW and upper half of the combined layer at selected times. The total settlement is the cumulative upward consolidation water flow at the selected times.

The calculations were performed using EXCEL<sup>®</sup> spreadsheets. An example of the calculation is shown in Attachment C. The calculated cumulative consolidation water variations with time for Areas 1 and 7 are presented in Figure 15. These two areas were selected because they have the smallest and largest calculated settlement corresponding to the condition with a 2-m dredge and 4-ft cap thickness and hence, likely to have the largest and smallest cumulative consolidation water flow, respectively. The calculated excess pore water pressure isochrones for Areas 1 and 7 are provided in Attachment D of this report. These isochrones indicated that the excess pore water pressure in SOLW dissipates much faster than in the combined layer. After most of the excess pore water

pressure in the SOLW has dissipated, the combined layer behaves similar to a doubly drained layer.

## 5. CONCLUSIONS

This report presents analyses performed to calculate the amount of consolidation settlement and the upward flow rate of consolidation water that may be expected following dredging and placement of a subaqueous cap in Remediation Area D. Based on the results of the analysis, the following conclusions can be made:

- The subsurface soils are expected to undergo consolidation settlement following placement of the cap. The magnitude of settlement largely depends on the dredging depth and cap thickness. The settlement increases when dredging depth decreases or cap thickness increases.
- The subsurface profiles have limited influence on the calculated settlement. The calculated settlements in all areas are in the range of 0 to 1.5 ft for a 30-year period using average or representative consolidation/compressibility parameters. The calculated settlements are in the range of 0 to 0.7 ft for a 2-year period in the area that has the largest calculated settlement for a 30-year period (i.e., Area 3).
- The calculated consolidation settlement is not very sensitive to the consolidation or compressibility parameters. A sensitivity analysis indicates that using reasonable upper bound values for consolidation/compressibility parameters increases the maximum settlement from 0.7 ft to 1.0 ft for the case with 2-m dredging and a 4-ft cap thickness over a 30-year period.
- Upward flow of consolidation water is expected after placement of the cap. The flow rate will be highest when the cap is placed and will decrease with time. For an average condition (i.e., 2-m dredge and 4-ft cap thickness) using average or representative consolidation/compressibility values, a total cumulative consolidation water of approximately 0.4 ft to 0.5 ft is expected within 30 years of cap material placement.

## REFERENCES

- Das, Braja M. (2008). “Advanced Soil Mechanics”. 3<sup>rd</sup> Edition. Taylor & Francis, Inc.
- Holtz and Kovacs. (1981). “An Introduction to Geotechnical Engineering”. Prentice-Hall, Inc., Englewood Cliffs, N. J., 733 p.
- Geosyntec Consultants. (2009). “Summary of Subsurface Stratigraphy and Material Properties”. A report summarizing the subsurface condition and material properties in SMU 1 and WB-B/HB area.
- Parsons. (2007). “Onondaga Lake Pre-Design Investigation: Phase I Data Summary Report”. May 2007.
- Parsons. (2009). “Onondaga Lake Pre-Design Investigation: Phase II Data Summary Report”. August 2009.
- Znidarcic, D., Abu-Hejleh, A.N., Fairbanks, T. and Robertson A. (1992). “Seepage-Induced Consolidation Test; Equipment Description and Users Manual”. Prepared for Florida Institute of Phosphate Research, University of Colorado, Boulder.

# TABLES

**Table 1.  $C_{ce}$  and  $C_{re}$  from Oedometer Tests for SOLW.**

Sample Location ID	Depth (ft)	Initial Void Ratio $e_0$	$C_c$	$C_r$	$C_{ce}^{[1]}$	$C_{re}^{[1]}$
OL-STA-10025	7-9	4.53	0.18	0.02	0.033	0.0038
OL-STA-10026	7-9	3.17	0.14	0.03	0.033	0.0065
OL-STA-10019	12.5-14.5	4.24	0.02	0.01	0.004	0.0023
OL-STA-10023	13-15	3.38	0.17	0.02	0.039	0.0054
OL-STA-10024	15-17	3.08	0.16	0.02	0.039	0.0047
OL-STA-10024	30-32	4.93	0.10	0.03	0.016	0.0054
OL-STA-10014	34.5-36.5	3.05	0.19	0.01	0.047	0.0036
Mean Value					0.030	0.0045
Maximum Value					0.047	0.0065
Minimum Value					0.004	0.0023
Standard Deviation					0.015	0.0014
Mean plus Standard Deviation					0.045	0.0031
Mean minus Standard Deviation					0.015	0.0059

Notes:

[1].  $C_{ce}$  and  $C_{re}$  are modified compression index and recompression index, respectively. They are calculated as follows:  $C_{ce} = C_c / (1+e_0)$  and  $C_{re} = C_r / (1+e_0)$ .

[2].  $C_c$  and  $C_{ce}$  values correspond to low stress range only.

**Table 2.  $C_{ce}$  and  $C_{re}$  from Oedometer Tests for Marl.**

Sample Location ID	Depth (ft)	Initial Void Ratio $e_0$	$C_c$	$C_r$	$C_{ce}^{[1]}$	$C_{re}^{[1]}$
OL-STA-20001	20-22	1.87	0.37	0.02	0.127	0.0082
OL-STA-20007	23-25	1.89	0.41	0.03	0.142	0.0113
OL-STA-20004	36.6-38.6	0.90	0.16	0.02	0.083	0.0103
Mean Value					0.117	0.0099
Maximum Value					0.142	0.0110
Minimum Value					0.083	0.0080
Standard Deviation					0.031	0.0016
Mean plus Standard Deviation					0.148	0.0115
Mean minus Standard Deviation					0.087	0.0083

Note:

[1].  $C_{ce}$  and  $C_{re}$  are modified compression index and recompression index, respectively. They are calculated as follows:  $C_{ce} = C_c / (1+e_0)$  and  $C_{re} = C_r / (1+e_0)$ .



**Table 3.  $C_{ce}$  and  $C_{re}$  from Oedometer Tests for Silt and Clay in SMU 1.**

Sample Location ID	Depth (ft)	Initial Void Ratio $e_0$	$C_c$	$C_r$	$C_{ce}^{[1]}$	$C_{re}^{[1]}$
OL-STA-10013	41-43	1.60	0.51	0.06	0.195	0.0228
OL-STA-10018	48-50	1.06	0.36	0.03	0.175	0.0151
OL-STA-10023	50-52	1.94	0.73	0.07	0.248	0.0255
OL-STA-10026	50-52	1.99	0.69	0.09	0.229	0.0297
OL-STA-10025	52-54	1.88	0.65	0.08	0.227	0.0295
OL-STA-10022	64-66	1.85	0.70	0.06	0.246	0.0212
OL-STA-10024	64-66	1.81	0.57	0.09	0.204	0.0330
OL-STA-10017	28-30	2.74	0.94	0.13	0.252	0.0353
OL-STA-10108	64-66	1.91	0.74	0.06	0.254	0.0206
OL-STA-10108	68-70	1.86	0.58	0.05	0.203	0.0175
Mean Value					0.223	0.0250
Maximum Value					0.254	0.0353
Minimum Value					0.175	0.0151
Standard Deviation					0.028	0.0067
Mean plus Standard Deviation					0.251	0.0317
Mean minus Standard Deviation					0.196	0.0183

Note:

[1].  $C_{ce}$  and  $C_{re}$  are modified compression index and recompression index, respectively. They are calculated as follows:  $C_{ce} = C_c / (1+e_0)$  and  $C_{re} = C_r / (1+e_0)$ .

**Table 4.  $C_{ce}$  and  $C_{re}$  from Oedometer Tests for Silt and Clay in SMU 2.**

Sample Location ID	Depth (ft)	Initial Void Ratio $e_0$	$C_c$	$C_r$	$C_{ce}^{[1]}$	$C_{re}^{[1]}$
OL-STA-20007	38.6-40.6	1.33	0.49	0.05	0.210	0.0222
OL-STA-20001	44.9-46.9	0.95	0.26	0.04	0.134	0.0223
OL-STA-20018	47-49	0.91	0.23	0.02	0.119	0.0090
Mean Value					0.154	0.0179
Maximum Value					0.210	0.022
Minimum Value					0.119	0.009
Standard Deviation					0.049	0.0076
Mean plus Standard Deviation					0.203	0.0255
Mean minus Standard Deviation					0.106	0.0102

Note:

[1].  $C_{ce}$  and  $C_{re}$  are modified compression index and recompression index, respectively. They are calculated as follows:  $C_{ce} = C_c / (1+e_0)$  and  $C_{re} = C_r / (1+e_0)$ .

**Table 5. Summary of the Material Properties used in Analysis.**

Materials	Unit Weight (pcf)	Consolidation Parameters				Hydraulic Conductivity (cm/s)
		$C_{ce}$	$C_{re}$	$C_{ae}$	$c_v$ (ft <sup>2</sup> /d)	
Cap	120	N/A	N/A	N/A	N/A	N/A
SOLW	81	0.030 <sup>[1]</sup>	0.0045	0.0011	3.500	$1 \times 10^{-5}$
Marl	98	0.117	0.0099	0.0050	0.090 (SMU 1) 0.100 (SMU 2) <sup>[2]</sup>	$1 \times 10^{-7}$
Silt and Clay (SMU 1)	108	0.223	0.0250	0.0100	0.090	$1 \times 10^{-7}$
Silt and Clay (SMU 2)	108	0.154	0.0179	0.0050	0.100	$1 \times 10^{-7}$

Notes:

[1].  $C_{ce}$  value corresponds to low stress range only.

[2]. The interpreted  $c_v$  of Marl is 0.135 ft<sup>2</sup>/d as presented in Figure 9. However, for the purpose of analysis, the  $c_v$  of Marl was assumed to be the same as Silt and Clay (i.e., 0.09 and 0.1 ft<sup>2</sup>/d in SMUs 1 and 2, respectively) in settlement calculations, as presented in Section 4.3.


**Table 6. Selected Reasonable Upper and Lower Bound Values for Consolidation Parameters.**

Material	$C_{ce}$	$C_{re}$	$C_{ae}$	$c_v$ (ft <sup>2</sup> /d)
Selected Reasonable Upper Bound Values				
SOLW	0.045	0.0059	0.0030	7.000
Marl	0.142	0.0110	0.0080	0.130 (SMU 1) 0.230 (SMU 2) <sup>[1]</sup>
Silt and Clay (SMU 1)	0.251	0.0317	0.0130	0.130
Silt and Clay (SMU 2)	0.203	0.0220	0.0070	0.230
Selected Reasonable Lower Bound Values				
SOLW	0.015	0.0031	0.0003	0.050 <sup>[2]</sup>
Marl	0.087	0.0083	0.0025	0.050 <sup>[2]</sup>
Silt and Clay (SMU 1)	0.196	0.0183	0.0070	0.050
Silt and Clay (SMU 2)	0.119	0.0102	0.0040	0.050

Notes:

- [1]. The interpreted reasonable upper bound value of  $c_v$  of Marl is 0.15 ft<sup>2</sup>/d, as presented in Figure 9. However, for the purpose of analysis, the reasonable upper bound value of  $c_v$  of Marl was assumed the same as Silt and Clay (i.e., 0.13 and 0.23 ft<sup>2</sup>/d in SMUs 1 and 2, respectively) in the settlement calculations, as presented in Section 4.3.
- [2]. The interpreted reasonable lower bound values of  $c_v$  of SOLW and Marl are 0.1 and 0.12 ft<sup>2</sup>/d, respectively, as presented in Figures 8 and 9. However, for the purpose of analysis, the reasonable lower bound values of  $c_v$  of SOLW and Marl were assumed the same as Silt and Clay (i.e., 0.05 ft<sup>2</sup>/d) in the settlement calculations, as presented in Section 4.3.


# FIGURES



**Figure 1. Remediation Area D.**




### Figure 2. Areas and Subsurface Layer Thicknesses.



**Figure 3. Comparison of Results from Conventional Oedometer Tests and SIC Tests.**






**Figure 4. Interpretation of Modified Secondary Compression Index for SOLW.**

Note:


The ratio of  $\sigma_v'/\sigma_p'$  of SOLW in the field before and after capping was estimated to be between 0.1 and 1 according to the assumed subsurface layer thicknesses.



**Figure 5. Interpretation of Modified Secondary Compression Index for Marl.**

Note:


The ratio of  $\sigma_v'/\sigma_p'$  of Marl in the field before and after capping was estimated to be between 0.7 and 3 according to the assumed subsurface layer thicknesses.



**Figure 6. Interpretation of Modified Secondary Compression Index for Silt and Clay in SMU 1.**

Note:


The ratio of  $\sigma_v'/\sigma_p''$  of Silt and Clay in the field before and after capping was estimated to be between 0.9 and 3 according to the assumed subsurface layer thicknesses.



**Figure 7. Interpretation of Modified Secondary Compression Index for Silt and Clay in SMU 2.**

Note:


The ratio of  $\sigma_v'/\sigma_p'$  of Silt and Clay in the field before and after capping was estimated to be between 0.9 and 3 according to the assumed subsurface layer thicknesses.



**Figure 8. Interpretation of Coefficient of Consolidation Index for SOLW.**

Note:


The ratio of  $\sigma_v'/\sigma_p'$  of SOLW in the field before and after capping was estimated to be between 0.1 and 1 according to the assumed subsurface layer thicknesses.



**Figure 9. Interpretation of Coefficient of Consolidation Index for Marl.**

Note:


The ratio of  $\sigma_v'/\sigma_p'$  of Marl in the field before and after capping was estimated to be between 0.7 and 3 according to the assumed subsurface layer thicknesses.



**Figure 10. Interpretation of Coefficient of Consolidation Index for Silt and Clay in SMU 1.**

Note:

The ratio of  $\sigma_v'/\sigma_p'$  of Silt and Clay in the field before and after capping was estimated to be between 0.9 and 3 according to the assumed subsurface layer thicknesses.




**Figure 11. Interpretation of Coefficient of Consolidation Index for Silt and Clay in SMU 2.**


Note:

The ratio of  $\sigma'_v/\sigma'_p$  of Silt and Clay in field before and after capping was estimated to be between 0.9 and 3 according to the assumed subsurface layer thicknesses.









(a)



(b)

**Figure 12. Finite difference method based numerical solution for the 1-D consolidation equation: (a) for nodes within homogeneous layers; and (b) for interface node between 2 layers. Note that the consolidation water flow direction is vertical. (source: Das, 2008)**



**Figure 13. Settlement Analysis Results for Areas 1 to 12 for 30-Year Period.**




Figure 13. Settlement Analysis Results for Areas 1 to 12 for 30-Year Period (continued).






Figure 13. Settlement Analysis Results for Areas 1 to 12 for 30-Year Period (continued).



**Figure 14. Settlement Analysis Results for Area 3 for 2-Year Period.**




**Figure 15. Calculated Cumulative Consolidation Water Flow.**

Note:

Calculations were performed for 2 m dredge and 4 ft thick cap.

# ATTACHMENT A

## SUBSURFACE LAYER THICKNESS CONTOURS




**Figure A1. The Thickness of SOLW in Remediation Area D**

Note:

1. The subsurface thickness contours were developed based on the elevations of each layer from the boring logs provided by Parsons, as presented in Section 2.
2. The subsurface thickness in the area that is not covered by the contours presented in this figure was estimated based on boring logs provided by Parsons.






**Figure A2. The Thickness of Marl in Remediation Area D**

Note:

1. The subsurface thickness contours were developed based on the elevations of each layer from the boring logs provided by Parsons, as presented in Section 2.
2. The subsurface thickness in the area that is not covered by the contours presented in this figure was estimated based on boring logs provided by Parsons.



**Figure A3. The Thickness of Silt and Clay in Remediation Area D**

Note:

1. The subsurface thickness contours were developed based on the elevations of each layer from the boring logs provided by Parsons. The bottom of Silt and Clay was below the depth of the shallow borings and was developed based on a limited number of borings that went to deeper depths in the ILWD, as presented in Section 2.
2. The subsurface thickness in the area that is not covered by the contours presented in this figure was estimated based on boring logs provided by Parsons.

## ATTACHMENT B

# CONVENTIONAL OEDOMETER TEST RESULTS SUMMARY

### Summary of Consolidation Test Data – Phase I PDI

Location ID	Field Sample ID	Depth (ft)	Average Depth (ft)	Compression Index (Cc)	Recompression Index (Cr)	Initial Void Ratio (e <sub>o</sub> )	Initial Water Content (%)	Preconsolidation Pressure (tsf)
OL-STA-10013	OL-0110-05	41-43	42	0.51	0.06	1.60	57.6	0.6
OL-STA-10014	OL-0110-08	34.5-36.5	35.5	0.94	0.01	3.05	113.1	0.6
OL-STA-10017	OL-0110-20	28-30	29	0.94	0.13	2.74	103.7	0.3
OL-STA-10018	OL-0110-27	48-50	49	0.36	0.03	1.06	36.5	0.7
OL-STA-10019	OL-0110-30	12.5-14.5	13.5	0.08	0.01	4.24	148.7	1.0
OL-STA-10022	OL-0110-49	64-66	65	0.70	0.06	1.85	67.2	0.8
OL-STA-10023	OL-0052-06	13-15	14	1.59	0.02	3.38	142.2	0.5
OL-STA-10023	OL-0052-04	50-52	51	0.73	0.07	1.94	72.5	0.9
OL-STA-10024	OL-0052-07	15-17	16	1.18	0.02	3.08	120.9	0.8
OL-STA-10024	OL-0052-09	30-32	31	2.84	0.03	4.93	180.0	1.4
OL-STA-10024	OL-0052-12	64-66	65	0.57	0.09	1.81	63.4	0.6
OL-STA-10025	OL-0052-13	7-9	8	2.04	0.02	4.53	183.6	0.9
OL-STA-10025	OL-0052-16	52-54	53	0.65	0.08	1.88	70.3	0.7
OL-STA-10026	OL-0052-19	7-9	8	1.22	0.03	3.17	105.7	0.9
OL-STA-10026	OL-0052-22	50-52	51	0.69	0.09	1.99	76.5	0.7
OL-STA-20001	OL-0072-07	20-22	21	0.37	0.02	1.87	64.2	0.3
OL-STA-20001	OL-0072-09	44.9-46.9	45.9	0.26	0.04	0.95	32.7	0.5
OL-STA-20004	OL-0072-01	12-14	13	0.72	0.01	2.91	102.3	0.3
OL-STA-20004	OL-0072-02	36.6-38.6	37.6	0.16	0.02	0.90	31.4	0.4
OL-STA-20007	OL-0072-04	23-25	24	0.41	0.03	1.89	65.8	0.3
OL-STA-20007	OL-0072-05	38.6-40.6	39.6	0.49	0.05	1.33	48.6	0.5
OL-STA-20016	OL-0110-52	27-29	28	0.19	0.04	0.89	30.9	0.4
OL-STA-20017	OL-0110-57	10-12	11	0.51	0.01	1.42	37.2	0.4
OL-STA-20017	OL-0110-59	42-44	43	0.22	0.03	0.87	31.1	0.6
OL-STA-20018	OL-0110-55	47-49	48	0.23	0.02	0.91	32.7	0.7

### Summary of Consolidation Test Data – Phase II PDI

Location ID	Field Sample ID	Depth (ft)	Average Depth (ft)	Compression Index (C <sub>c</sub> )	Recompression Index (C <sub>r</sub> )	Modified Compression Index (C <sub>cc</sub> )	Modified Recompression Index (C <sub>re</sub> )	Initial Void Ratio (e <sub>o</sub> )	Initial Water Content (%)	Preconsolidation Pressure (psf)
OL-STA-10108	OL-0267-01	64-66	65	0.74	0.06	0.25	0.02	1.91	70.8	1702
OL-STA-10108	OL-0267-02	68-70	69	0.58	0.05	0.20	0.02	1.86	65.3	1032 (disturbed sample)

Notes:

1. The C<sub>c</sub> values of SOLW in this table correspond to high stress (i.e., >1000 psf) range and were not used in analysis.
2. The modified compression index C<sub>cc</sub> and recompression index C<sub>re</sub> are calculated as follows:  $C_{cc} = C_c / (1 + e_o)$  and  $C_{re} = C_r / (1 + e_o)$ .
3. These summary tables were provided to Geosyntec by Parsons.

# ATTACHMENT C

## EXAMPLES OF CALCULATIONS

(For Area 7 with 2 m dredge and 4 ft thick cap)

## An Example of Settlement Calculations

Input:

Dredging Depth 6.6 ft

Consider Total Settlement in 30 years

Soil Layers	Thickness (ft)	Unit Weight (pcf)	OCR	$C_{\text{ce}}$	$C_{\text{re}}$	$C_{\alpha}$	Coef. of Con. $c_v$ (ft <sup>2</sup> /d)	Time of 90% primary con. (years)	$t_2/t_1$ for Secondary Con.	# of Sublayers
Cap	<span style="color: red;">4</span>	<span style="color: red;">120</span>								
SOLW	<span style="color: red;">45</span>	<span style="color: red;">81</span>	<span style="color: red;">1</span>	<span style="color: red;">0.030</span>	<span style="color: red;">0.0045</span>	<span style="color: red;">0.0011</span>	<span style="color: red;">3.500</span>	1.3	22.3	18
Marl	<span style="color: red;">0</span>	<span style="color: red;">98</span>	<span style="color: red;">1</span>	<span style="color: red;">0.117</span>	<span style="color: red;">0.0099</span>	<span style="color: red;">0.0050</span>	<span style="color: red;">0.090</span>	5.8	5.2	0
Silt/Clay	<span style="color: red;">30</span>	<span style="color: red;">108</span>	<span style="color: red;">1</span>	<span style="color: red;">0.223</span>	<span style="color: red;">0.0250</span>	<span style="color: red;">0.0100</span>	<span style="color: red;">0.090</span>	5.8	5.2	6
Water		<span style="color: red;">62.4</span>								

Calculated Settlement (ft):

	Primary Settlement	Secondary Settlement	Total Settlement
SOLW	0.158	0.057	0.215
Marl	0.000	0.000	0.000
Silt/Clay	0.242	0.215	0.457
Total	0.40	0.27	<span style="color: red;"><b><u>0.67</u></b></span>

Calculation for SOLW			
Layer No.	1	Layer No.	5
Layer Thickness, m / ft	2.133333	Layer Thickness, m / ft	2.133333
Midpoint Depth from Dredge Bot, m/ft	1.066667	Midpoint Depth from Dredge Bot, m/ft	9.6
Effective Stress Before Dredging, KPa/psf	142.6	Effective Stress Before Dredging, KPa/psf	301.32
Initial Effective Stress, KPa/psf	19.84	Initial Effective Stress, KPa/psf	178.56
Final Effective Stress, KPa/psf	250.24	Final Effective Stress, KPa/psf	408.96
OCR	1	OCR	1
Preconsolidation Pressure, KPa/psf	142.6	Preconsolidation Pressure, KPa/psf	301.32
Modified Primary Compression Index, $C_{cc}$	0.03	Modified Primary Compression Index, $C_{cc}$	0.03
Modified Recompression Index, $C_{re}$	0.0045	Modified Recompression Index, $C_{re}$	0.0045
Modified Secondary Compression Index, $C_{\alpha e}$	0.0011	Modified Secondary Compression Index, $C_{\alpha e}$	0.0011
ratio of $t_2 / t_1$	22.3	ratio of $t_2 / t_1$	22.3
Settlements		Settlements	
Primary Settlement, (m / ft)	0.024	Primary Settlement, (m / ft)	0.011
Secondary Settlement (m / ft)	0.003	Secondary Settlement (m / ft)	0.003
Total Settlement (m / ft)	0.027	Total Settlement (m / ft)	0.014
Layer No.	2	Layer No.	6
Layer Thickness, m / ft	2.133333	Layer Thickness, m / ft	2.133333
Midpoint Depth from Dredge Bot, m/ft	3.2	Midpoint Depth from Dredge Bot, m/ft	11.733333
Effective Stress Before Dredging, KPa/psf	182.28	Effective Stress Before Dredging, KPa/psf	341
Initial Effective Stress, KPa/psf	59.52	Initial Effective Stress, KPa/psf	218.24
Final Effective Stress, KPa/psf	289.92	Final Effective Stress, KPa/psf	448.64
OCR	1	OCR	1
Preconsolidation Pressure, KPa/psf	182.28	Preconsolidation Pressure, KPa/psf	341
Modified Primary Compression Index, $C_{cc}$	0.03	Modified Primary Compression Index, $C_{cc}$	0.03
Modified Recompression Index, $C_{re}$	0.0045	Modified Recompression Index, $C_{re}$	0.0045
Modified Secondary Compression Index, $C_{\alpha e}$	0.0011	Modified Secondary Compression Index, $C_{\alpha e}$	0.0011
ratio of $t_2 / t_1$	22.3	ratio of $t_2 / t_1$	22.3
Settlements		Settlements	
Primary Settlement, (m / ft)	0.018	Primary Settlement, (m / ft)	0.009
Secondary Settlement (m / ft)	0.003	Secondary Settlement (m / ft)	0.003
Total Settlement (m / ft)	0.021	Total Settlement (m / ft)	0.013
Layer No.	3	Layer No.	7
Layer Thickness, m / ft	2.133333	Layer Thickness, m / ft	2.133333
Midpoint Depth from Dredge Bot, m/ft	5.333333	Midpoint Depth from Dredge Bot, m/ft	13.866667
Effective Stress Before Dredging, KPa/psf	221.96	Effective Stress Before Dredging, KPa/psf	380.68
Initial Effective Stress, KPa/psf	99.2	Initial Effective Stress, KPa/psf	257.92
Final Effective Stress, KPa/psf	329.6	Final Effective Stress, KPa/psf	488.32
OCR	1	OCR	1
Preconsolidation Pressure, KPa/psf	221.96	Preconsolidation Pressure, KPa/psf	380.68
Modified Primary Compression Index, $C_{cc}$	0.03	Modified Primary Compression Index, $C_{cc}$	0.03
Modified Recompression Index, $C_{re}$	0.0045	Modified Recompression Index, $C_{re}$	0.0045
Modified Secondary Compression Index, $C_{\alpha e}$	0.0011	Modified Secondary Compression Index, $C_{\alpha e}$	0.0011
ratio of $t_2 / t_1$	22.3	ratio of $t_2 / t_1$	22.3
Settlements		Settlements	
Primary Settlement, (m / ft)	0.014	Primary Settlement, (m / ft)	0.009
Secondary Settlement (m / ft)	0.003	Secondary Settlement (m / ft)	0.003
Total Settlement (m / ft)	0.018	Total Settlement (m / ft)	0.012
Layer No.	4	Layer No.	8
Layer Thickness, m / ft	2.133333	Layer Thickness, m / ft	2.133333
Midpoint Depth from Dredge Bot, m/ft	7.466667	Midpoint Depth from Dredge Bot, m/ft	16
Effective Stress Before Dredging, KPa/psf	261.64	Effective Stress Before Dredging, KPa/psf	420.36
Initial Effective Stress, KPa/psf	138.88	Initial Effective Stress, KPa/psf	297.6
Final Effective Stress, KPa/psf	369.28	Final Effective Stress, KPa/psf	528
OCR	1	OCR	1
Preconsolidation Pressure, KPa/psf	261.64	Preconsolidation Pressure, KPa/psf	420.36
Modified Primary Compression Index, $C_{cc}$	0.03	Modified Primary Compression Index, $C_{cc}$	0.03
Modified Recompression Index, $C_{re}$	0.0045	Modified Recompression Index, $C_{re}$	0.0045
Modified Secondary Compression Index, $C_{\alpha e}$	0.0011	Modified Secondary Compression Index, $C_{\alpha e}$	0.0011
ratio of $t_2 / t_1$	22.3	ratio of $t_2 / t_1$	22.3
Settlements		Settlements	
Primary Settlement, (m / ft)	0.012	Primary Settlement, (m / ft)	0.008
Secondary Settlement (m / ft)	0.003	Secondary Settlement (m / ft)	0.003
Total Settlement (m / ft)	0.015	Total Settlement (m / ft)	0.01

Layer No. 9		Layer No. 14	
Layer Thickness, m / ft	2.1333333	Layer Thickness, m / ft	2.1333333
Midpoint Depth from Dredge Bot, m/ft	18.133333	Midpoint Depth from Dredge Bot, m/ft	28.8
Effective Stress Before Dredging, KPa/psf	460.04	Effective Stress Before Dredging, KPa/psf	658.44
Initial Effective Stress, KPa/psf	337.28	Initial Effective Stress, KPa/psf	535.68
Final Effective Stress, KPa/psf	567.68	Final Effective Stress, KPa/psf	766.08
OCR	1	OCR	1
Preconsolidation Pressure, KPa/psf	460.04	Preconsolidation Pressure, KPa/psf	658.44
Modified Primary Compression Index, $C_{cc}$	0.03	Modified Primary Compression Index, $C_{cc}$	0.03
Modified Recompression Index, $C_{re}$	0.0045	Modified Recompression Index, $C_{re}$	0.0045
Modified Secondary Compression Index, $C_{\alpha\alpha}$	0.0011	Modified Secondary Compression Index, $C_{\alpha\alpha}$	0.0011
ratio of $t_2 / t_1$	22.3	ratio of $t_2 / t_1$	22.3
Settlements		Settlements	
Primary Settlement, (m / ft)	0.007	Primary Settlement, (m / ft)	0.005
Secondary Settlement (m / ft)	0.003	Secondary Settlement (m / ft)	0.003
Total Settlement (m / ft)	0.010	Total Settlement (m / ft)	0.008

Layer No. 10		Layer No. 15	
Layer Thickness, m / ft	2.1333333	Layer Thickness, m / ft	2.1333333
Midpoint Depth from Dredge Bot, m/ft	20.266667	Midpoint Depth from Dredge Bot, m/ft	30.933333
Effective Stress Before Dredging, KPa/psf	499.72	Effective Stress Before Dredging, KPa/psf	698.12
Initial Effective Stress, KPa/psf	376.96	Initial Effective Stress, KPa/psf	575.36
Final Effective Stress, KPa/psf	607.36	Final Effective Stress, KPa/psf	805.76
OCR	1	OCR	1
Preconsolidation Pressure, KPa/psf	499.72	Preconsolidation Pressure, KPa/psf	698.12
Modified Primary Compression Index, $C_{cc}$	0.03	Modified Primary Compression Index, $C_{cc}$	0.03
Modified Recompression Index, $C_{re}$	0.0045	Modified Recompression Index, $C_{re}$	0.0045
Modified Secondary Compression Index, $C_{\alpha\alpha}$	0.0011	Modified Secondary Compression Index, $C_{\alpha\alpha}$	0.0011
ratio of $t_2 / t_1$	22.3	ratio of $t_2 / t_1$	22.3
Settlements		Settlements	
Primary Settlement, (m / ft)	0.007	Primary Settlement, (m / ft)	0.005
Secondary Settlement (m / ft)	0.003	Secondary Settlement (m / ft)	0.003
Total Settlement (m / ft)	0.010	Total Settlement (m / ft)	0.008

Layer No. 11		Layer No. 16	
Layer Thickness, m / ft	2.1333333	Layer Thickness, m / ft	2.1333333
Midpoint Depth from Dredge Bot, m/ft	22.4	Midpoint Depth from Dredge Bot, m/ft	33.066667
Effective Stress Before Dredging, KPa/psf	539.4	Effective Stress Before Dredging, KPa/psf	737.8
Initial Effective Stress, KPa/psf	416.64	Initial Effective Stress, KPa/psf	615.04
Final Effective Stress, KPa/psf	647.04	Final Effective Stress, KPa/psf	845.44
OCR	1	OCR	1
Preconsolidation Pressure, KPa/psf	539.4	Preconsolidation Pressure, KPa/psf	737.8
Modified Primary Compression Index, $C_{cc}$	0.03	Modified Primary Compression Index, $C_{cc}$	0.03
Modified Recompression Index, $C_{re}$	0.0045	Modified Recompression Index, $C_{re}$	0.0045
Modified Secondary Compression Index, $C_{\alpha\alpha}$	0.0011	Modified Secondary Compression Index, $C_{\alpha\alpha}$	0.0011
ratio of $t_2 / t_1$	22.3	ratio of $t_2 / t_1$	22.3
Settlements		Settlements	
Primary Settlement, (m / ft)	0.006	Primary Settlement, (m / ft)	0.005
Secondary Settlement (m / ft)	0.003	Secondary Settlement (m / ft)	0.003
Total Settlement (m / ft)	0.009	Total Settlement (m / ft)	0.008

Layer No. 12		Layer No. 17	
Layer Thickness, m / ft	2.1333333	Layer Thickness, m / ft	2.1333333
Midpoint Depth from Dredge Bot, m/ft	24.533333	Midpoint Depth from Dredge Bot, m/ft	35.2
Effective Stress Before Dredging, KPa/psf	579.08	Effective Stress Before Dredging, KPa/psf	777.48
Initial Effective Stress, KPa/psf	456.32	Initial Effective Stress, KPa/psf	654.72
Final Effective Stress, KPa/psf	686.72	Final Effective Stress, KPa/psf	885.12
OCR	1	OCR	1
Preconsolidation Pressure, KPa/psf	579.08	Preconsolidation Pressure, KPa/psf	777.48
Modified Primary Compression Index, $C_{cc}$	0.03	Modified Primary Compression Index, $C_{cc}$	0.03
Modified Recompression Index, $C_{re}$	0.0045	Modified Recompression Index, $C_{re}$	0.0045
Modified Secondary Compression Index, $C_{\alpha\alpha}$	0.0011	Modified Secondary Compression Index, $C_{\alpha\alpha}$	0.0011
ratio of $t_2 / t_1$	22.3	ratio of $t_2 / t_1$	22.3
Settlements		Settlements	
Primary Settlement, (m / ft)	0.006	Primary Settlement, (m / ft)	0.004
Secondary Settlement (m / ft)	0.003	Secondary Settlement (m / ft)	0.003
Total Settlement (m / ft)	0.009	Total Settlement (m / ft)	0.007

Layer No. 13		Layer No. 18	
Layer Thickness, m / ft	2.1333333	Layer Thickness, m / ft	2.1333333
Midpoint Depth from Dredge Bot, m/ft	26.666667	Midpoint Depth from Dredge Bot, m/ft	37.333333
Effective Stress Before Dredging, KPa/psf	618.76	Effective Stress Before Dredging, KPa/psf	817.16
Initial Effective Stress, KPa/psf	496	Initial Effective Stress, KPa/psf	694.4
Final Effective Stress, KPa/psf	726.4	Final Effective Stress, KPa/psf	924.8
OCR	1	OCR	1
Preconsolidation Pressure, KPa/psf	618.76	Preconsolidation Pressure, KPa/psf	817.16
Modified Primary Compression Index, $C_{cc}$	0.03	Modified Primary Compression Index, $C_{cc}$	0.03
Modified Recompression Index, $C_{re}$	0.0045	Modified Recompression Index, $C_{re}$	0.0045
Modified Secondary Compression Index, $C_{\alpha\alpha}$	0.0011	Modified Secondary Compression Index, $C_{\alpha\alpha}$	0.0011
ratio of $t_2 / t_1$	22.3	ratio of $t_2 / t_1$	22.3
Settlements		Settlements	
Primary Settlement, (m / ft)	0.005	Primary Settlement, (m / ft)	0.004
Secondary Settlement (m / ft)	0.003	Secondary Settlement (m / ft)	0.003
Total Settlement (m / ft)	0.009	Total Settlement (m / ft)	0.007



# Calculation for Silt and Clay

Layer No.	1	Layer No.	4
Layer Thickness, m / ft	5	Layer Thickness, m / ft	5
Midpoint Depth from Top of Silt/Clay, m/ft	2.5	Midpoint Depth from Top of Silt/Clay, m/ft	17.5
Effective Stress Before Dredging, KPa/psf	951	Effective Stress Before Dredging, KPa/psf	1635
Initial Effective Stress, KPa/psf	828.24	Initial Effective Stress, KPa/psf	1512.24
Final Effective Stress, KPa/psf	1058.64	Final Effective Stress, KPa/psf	1742.64
OCR	1	OCR	1
Preconsolidation Pressure, KPa/psf	951	Preconsolidation Pressure, KPa/psf	1635
Modified Primary Compression Index, $C_{ce}$	0.223	Modified Primary Compression Index, $C_{ce}$	0.223
Modified Recompression Index, $C_{re}$	0.025	Modified Recompression Index, $C_{re}$	0.025
Modified Secondary Compression Index, $C_{\alpha e}$	0.01	Modified Secondary Compression Index, $C_{\alpha e}$	0.01
ratio of $t_2 / t_1$	5.2	ratio of $t_2 / t_1$	5.2
Settlements		Settlements	
Primary Settlement, (m / ft)	0.059	Primary Settlement, (m / ft)	0.035
Secondary Settlement (m / ft)	0.036	Secondary Settlement (m / ft)	0.036
Total Settlement (m / ft)	0.095	Total Settlement (m / ft)	0.071

Layer No.	2	Layer No.	5
Layer Thickness, m / ft	5	Layer Thickness, m / ft	5
Midpoint Depth from Top of Silt/Clay, m/ft	7.5	Midpoint Depth from Top of Silt/Clay, m/ft	22.5
Effective Stress Before Dredging, KPa/psf	1179	Effective Stress Before Dredging, KPa/psf	1863
Initial Effective Stress, KPa/psf	1056.24	Initial Effective Stress, KPa/psf	1740.24
Final Effective Stress, KPa/psf	1286.64	Final Effective Stress, KPa/psf	1970.64
OCR	1	OCR	1
Preconsolidation Pressure, KPa/psf	1179	Preconsolidation Pressure, KPa/psf	1863
Modified Primary Compression Index, $C_{ce}$	0.223	Modified Primary Compression Index, $C_{ce}$	0.223
Modified Recompression Index, $C_{re}$	0.025	Modified Recompression Index, $C_{re}$	0.025
Modified Secondary Compression Index, $C_{\alpha e}$	0.01	Modified Secondary Compression Index, $C_{\alpha e}$	0.01
ratio of $t_2 / t_1$	5.2	ratio of $t_2 / t_1$	5.2
Settlements		Settlements	
Primary Settlement, (m / ft)	0.048	Primary Settlement, (m / ft)	0.031
Secondary Settlement (m / ft)	0.036	Secondary Settlement (m / ft)	0.036
Total Settlement (m / ft)	0.084	Total Settlement (m / ft)	0.067

Layer No.	3	Layer No.	6
Layer Thickness, m / ft	5	Layer Thickness, m / ft	5
Midpoint Depth from Top of Silt/Clay, m/ft	12.5	Midpoint Depth from Top of Silt/Clay, m/ft	27.5
Effective Stress Before Dredging, KPa/psf	1407	Effective Stress Before Dredging, KPa/psf	2091
Initial Effective Stress, KPa/psf	1284.24	Initial Effective Stress, KPa/psf	1968.24
Final Effective Stress, KPa/psf	1514.64	Final Effective Stress, KPa/psf	2198.64
OCR	1	OCR	1
Preconsolidation Pressure, KPa/psf	1407	Preconsolidation Pressure, KPa/psf	2091
Modified Primary Compression Index, $C_{ce}$	0.223	Modified Primary Compression Index, $C_{ce}$	0.223
Modified Recompression Index, $C_{re}$	0.025	Modified Recompression Index, $C_{re}$	0.025
Modified Secondary Compression Index, $C_{\alpha e}$	0.01	Modified Secondary Compression Index, $C_{\alpha e}$	0.01
ratio of $t_2 / t_1$	5.2	ratio of $t_2 / t_1$	5.2
Settlements		Settlements	
Primary Settlement, (m / ft)	0.041	Primary Settlement, (m / ft)	0.028
Secondary Settlement (m / ft)	0.036	Secondary Settlement (m / ft)	0.036
Total Settlement (m / ft)	0.076	Total Settlement (m / ft)	0.063

# An Example Calculation of Upward Cumulative Consolidation Water Flow

## Loading

Cap thickness = 4 ft  
 Cap unit weight = 120 psf  
 Load = 230.4 psf

## Properties

Type	Top Layer SOLW	Bottom Layer Silt and Clay	
k =	1.0E-05	1.0E-07 cm/s	A = 0.7272
	1.8E-01	1.8E-03 ft/d	B = 2.0E+00
Cv =	3.50	0.09 ft <sup>2</sup> /d	C = 2.0E-02
H =	39	30 ft	
Cαε =	0.0011	0.0100	
t90 =	435	2500 days	
	1.2	6.8 years	

## Reference Values

zR =	69.0	69.0 ft
uR =	2.30	2.30 psf
tR =	1360	52900 days
	4	145 years

## Time Step

Select  $\delta t$  to ensure convergence of solution

$\delta t$ =	0.0030	0.0030 years
	1	1 days
$\delta t\text{-bar}$ =	8.05E-04	2.07E-05
$\delta z$ =	3	3 ft
$\delta z\text{-bar}$ =	0.04	0.04

bar  $\delta t_1/(\delta z)^2 =$  0.43 0.01 should be less than 0.5

		U-bar values																	
t (years)		0.00	0.00	0.01	0.01	0.01	0.01	0.02	0.02	0.02	0.02	0.03	0.03	0.03	0.04	0.04	0.04	0.05	0.05
t (days)		0	1	2	3	4	5	7	8	9	10	11	12	13	14	15	16	18	
t-bar		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	
Z (ft)	z-bar	s1	s2	s3	s4	s5	s6	s7	s8	s9	s10	s10	s10	s10	s10	s10	s10	s10	s10
	0	0.0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	3	0.0	100	57	51	42	39	35	33	30	29	27	26	25	24	23	22	22	21
	6	0.1	100	100	82	76	69	65	60	57	54	52	49	48	46	44	43	42	41
	9	0.1	100	100	100	92	89	84	80	77	74	71	68	66	64	62	61	59	58
	12	0.2	100	100	100	100	97	95	92	89	87	84	82	80	78	76	75	73	71
	15	0.2	100	100	100	100	100	99	98	96	94	93	91	89	88	86	85	83	82
	18	0.3	100	100	100	100	100	100	99	99	98	97	96	95	94	93	92	90	89
	21	0.3	100	100	100	100	100	100	100	100	99	99	99	98	97	96	96	95	94
	24	0.3	100	100	100	100	100	100	100	100	100	100	100	99	99	98	98	98	97
	27	0.4	100	100	100	100	100	100	100	100	100	100	100	100	100	99	99	99	99
	30	0.4	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	99
	33	0.5	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
	36	0.5	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
	39	0.6	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
	42	0.6	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
	45	0.7	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
	48	0.7	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
	51	0.7	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
	54	0.8	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
	57	0.8	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
	60	0.9	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
	63	0.9	100	100	100	100	100	100	100	100	100	100	100	99	99	99	99	99	99
	66	1.0	100	99	98	97	96	95	94	93	92	91	90	89	88	87	87	86	85
	69	1.0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Top Layer																			
	Initial Area =	3900	3900	3900	3900	3900	3900	3900	3900	3900	3900	3900	3900	3900	3900	3900	3900	3900	3900
	Current Area =	3700	3530	3468	3392	3342	3288	3244	3201	3162	3124	3090	3056	3024	2993	2963	2935	2907	
	U-ave=	5%	9%	11%	13%	14%	16%	17%	18%	19%	20%	21%	22%	22%	23%	24%	25%	25%	
	Final primary settlement (ft) =	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16
	Current primary settlement (ft) =	0.01	0.02	0.02	0.02	0.02	0.02	0.03	0.03	0.03	0.03	0.03	0.03	0.04	0.04	0.04	0.04	0.04	0.04
	Current secondary settlement (ft) =	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Current total settlement (ft) =	0.01	0.02	0.02	0.02	0.02	0.02	0.03	0.03	0.03	0.03	0.03	0.03	0.04	0.04	0.04	0.04	0.04	0.04
Bottom Layer																			
	Initial Area =	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000
	Current Area =	2900	2896	2891	2887	2883	2879	2875	2871	2867	2863	2859	2855	2852	2848	2845	2841	2837	
	U-ave=	3%	3%	4%	4%	4%	4%	4%	4%	4%	5%	5%	5%	5%	5%	5%	5%	5%	5%
	Final primary settlement (ft) =	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15
	Current primary settlement (ft) =	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
	Current secondary settlement (ft) =	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Current total settlement (ft) =	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
Total																			
	Total current settlement (ft) =	0.01	0.02	0.02	0.03	0.03	0.03	0.03	0.03	0.04	0.04	0.04	0.04	0.04	0.04	0.05	0.05	0.05	

Note: Due to the limited paper size, only part of the calculation sheet is shown here.

**U bar and settlement results summary**

Uave top	5%	16%	30%	51%	73%	93%	99%	100%	100%	100%
Uave bot	3%	4%	6%	12%	22%	41%	79%	98%	100%	100%
t (years)	0.00	0.02	0.07	0.23	0.54	1.29	4.21	10.54	18.97	30.00
t (days)	0.00	5.48	25.19	82.13	196.01	469.75	1536.29	3845.64	6924.78	10950.00
Z (ft)	t = 0, Ut=5%, Ub= t = 5 days, Ut=16%, Ub t = 25 days, Ut=30%, Ub= t = 82 days, Ut= t = 196 days, Lt = 1.3 years, Ut t = 4.2 years, Ut t = 10.5 years, Lt = 19.0 years, Lt = 30 years, Ut=100%, Ub=100%									
0	0	0	0	0	0	0	0	0	0	0
3	100	35	18	10	5	1	0	0	0	0
6	100	65	34	20	10	3	0	0	0	0
9	100	84	50	29	15	4	0	0	0	0
12	100	95	63	38	20	5	1	0	0	0
15	100	99	74	46	25	7	1	0	0	0
18	100	100	82	54	29	8	1	0	0	0
21	100	100	88	60	33	9	1	0	0	0
24	100	100	93	66	36	10	1	0	0	0
27	100	100	96	71	39	11	1	0	0	0
30	100	100	98	75	41	12	1	0	0	0
33	100	100	99	78	43	12	1	0	0	0
36	100	100	99	80	45	13	1	0	0	0
39	100	100	100	81	45	13	2	0	0	0
42	100	100	100	96	77	43	12	1	0	0
45	100	100	100	99	92	66	20	2	0	0
48	100	100	100	100	98	79	27	3	0	0
51	100	100	100	100	99	86	32	3	0	0
54	100	100	100	100	98	85	33	4	0	0
57	100	100	100	99	95	79	31	3	0	0
60	100	100	100	97	86	67	26	3	0	0
63	100	100	98	87	69	48	19	2	0	0
66	100	95	80	57	39	26	10	1	0	0
69	0	0	0	0	0	0	0	0	0	0
Cumulative Upward Consc	0.01	0.03	0.06	0.10	0.15	0.21	0.30	0.37	0.42	0.46


# ATTACHMENT D

## CALCULATED EXCESS PORE WATER PRESSURE ISOCHRONES


Note:

In the charts presented herein,  $U_t$  = the average degree of consolidation of top layer (i.e., SOLW);  $U_b$  = the average degree of consolidation of bottom layer (i.e., Marl + Silt and Clay).

### Area 1 (6.6' dredge, 4' cap)



### Area 7 (6.6' dredge, 4' cap)



*Prepared for*

**Parsons**

301 Plainfield Road, Suite 350  
Syracuse, New York 13212

**ONONDAGA LAKE WB-B/HB IRM OUTBOARD AREA  
CAP-INDUCED SETTLEMENT EVALUATION  
AN ADDENDUM TO THE REPORT TITLED  
“CAP-INDUCED SETTLEMENT EVALUATION FOR  
REMEDIATION AREA D”**

**SYRACUSE AND GEDDES, NEW YORK**

*Prepared by*

**Geosyntec**   
consultants

engineers | scientists | innovators

1255 Roberts Boulevard, Suite 200  
Kennesaw, Georgia 30144

Project Number: GJ4741

January 2011

## TABLE OF CONTENTS

1.	INTRODUCTION .....	1
2.	SUBSURFACE CONDITIONS .....	1
3.	MATERIAL PROPERTIES .....	2
4.	SETTLEMENT CALCULATIONS .....	2
4.1	Methodology .....	2
4.2	Removal Depth and Cap Thickness .....	2
4.3	Settlement Calculations and Results .....	2

## LIST OF TABLES

Table 1. Summary of the Material Properties used in Settlement Calculations

## LIST OF FIGURES

Figure 1. WB-B/HB Outboard Area Plan

Figure 2. Settlement Calculation Results for the 30-Year Period

Figure 3. Settlement Calculation Results for the 2-Year Period (Subarea 7 Only)

## LIST OF ATTACHMENTS

Attachment A. Subsurface Layer Thickness Contours

Attachment B. Interpretation of Consolidation Parameters of Subsurface Materials

Attachment C. Example Settlement Calculation



## 1. INTRODUCTION

This report was prepared as an addendum to the report titled “*Cap-Induced Settlement Evaluation for Remediation Area D*” (referred to as the RA-D Cap Settlement Report) dated January 2011. It presents the evaluation of the consolidation settlement anticipated after removal and capping in the Wastebed B/Harbor Brook (WB-B/HB) Outboard Area. Specifically, this report presents the total settlement (including the primary and the secondary settlement) at the end of 30 years after capping for the entire Outboard Area and at the end of two years after capping for the subarea with the highest estimated settlement.

The Outboard Area is a 16-acre strip of land that lies between Onondaga Lake and the Wastebed B barrier wall alignment, and includes the mouth of Harbor Brook and areas of wetlands along the lake shoreline, as shown in Figure 1. The Outboard Area is part of the WB-B/HB Site, which is a subsite of the Onondaga Lake Superfund site. Based on the wetland restoration concepts advanced as part of the *Draft Habitat Plan* (Parsons, 2009), it is anticipated that the remedy for this area will include removal of material above and below the water table, construction of an isolation cap, and habitat restoration. The assumptions used for the analyses presented herein are based on the minimum required sediment removal to allow cap construction and habitat restoration, as developed and documented in the main text of the *Capping, Dredging, and Habitat Design*.

The remainder of this report presents: (i) subsurface conditions; (ii) material properties; and (iii) settlement calculations and results for the Outboard Area.

## 2. SUBSURFACE CONDITIONS

Information regarding the subsurface stratigraphy in the Outboard Area was presented in two calculation packages prepared previously by Geosyntec: “*Summary of Subsurface Stratigraphy and Material Properties*” for the West Wall design (referred to as the West Wall Data Package) and “*Summary of Subsurface Stratigraphy and Material Properties*” for the East Wall design (referred to as the East Wall Data Package). For the purpose of the settlement calculations presented herein, the Outboard Area was divided into 8 subareas based on the thicknesses of the Fill, SOLW, Marl, and Silt and Clay layers. Subareas 1 through 6 are located in the outboard area near the West Wall; while Subareas 7 and 8 are located in the outboard area near the East Wall.

These subareas and the selected representative thicknesses of the subsurface layers are presented in Figure 1. The thickness contours for each of the subsurface layers in the outboard area are presented in Attachment A of this report.

### **3. MATERIAL PROPERTIES**

Information regarding the unit weights of the subsurface materials in the Outboard Area was presented in the West Wall Data Package and the East Wall Data Package. The consolidation parameters were interpreted from the laboratory test data and presented in Attachment B of this report. The material properties used for the settlement calculations are summarized in Table 1.

### **4. SETTLEMENT CALCULATIONS**

#### **4.1 Methodology**

The same methodology presented in the RA-D Cap Settlement Report was used in the settlement calculations presented herein.

#### **4.2 Removal Depth and Cap Thickness**

The range in removal depths and cap thicknesses assumed for this analysis are based on the design presented in the main text of the *Capping, Dredging, and Habitat Design*.

#### **4.3 Settlement Calculations and Results**

The settlement calculation results for the 30-year period are presented in Figure 2. For each subarea, calculations were performed for a combination of five removal depths (i.e., 0 ft, 3 ft, 6 ft, 9 ft, and 12 ft) and three cap thicknesses (i.e., 2 ft, 4 ft, and 6 ft). Additional settlement calculations were performed for the 2-year period after capping. Subarea 7 was selected because it has the largest calculated settlement for the 30-year period. The results for Subarea 7 for the 2-year period are presented in Figure 3.

An example calculation using an Excel<sup>®</sup> spreadsheet is included in Attachment C of this report. The Excel<sup>®</sup> spreadsheets for all the settlement calculations presented in this report are included in the attached CD.

It should be noted that the following assumptions were made in the settlement calculations:

- The SOLW, Marl, and Silt and Clay layers were assumed as one layer for the purpose of calculating the time needed to reach 90% primary consolidation because the  $c_v$  values for these three layers are similar and much smaller than that of the Fill layer.
- The Fill layer was assumed to have single drainage due to the relatively low permeability layer underneath. The combined SOLW, Marl, and Silt and Clay layer was assumed to have double drainage due to the relatively high permeability materials above (i.e., Fill) and underneath (i.e., Silt and Sand).

The settlement calculation results indicate that generally the calculated settlement increases as the removal depth decreases or the cap thickness increases. However, the calculated settlement becomes less sensitive to either the removal depth or the cap thickness when the removal depth is greater than approximately 6 ft.

# TABLES

Table 1. Summary of Material Properties used in Settlement Calculations

Area	Material	Unit Weight (pcf)	Recommended Consolidation Parameters			
			$C_{ce}$	$C_{re}$	$C_{\alpha e}$	$c_v$ (ft <sup>2</sup> /d)
Outboard Area near West Wall (Subareas 1 through 6)	Fill <sup>[1]</sup>	105	0.061	0.006	0.0003	4.50
	SOLW	80	0.042 <sup>[2]</sup>	0.003	0.0006	0.60 <sup>[3]</sup>
	Marl	101	0.152	0.010	0.0008	0.50
	Silt and Clay	118	0.117	0.013	0.0015	0.15
Outboard Area near East Wall (Subareas 7 and 8)	Fill	92	0.061	0.006	0.0003	4.50
	Marl	97	0.176	0.010	0.0030	0.25 <sup>[3]</sup>
	Silt and Clay	111	0.129	0.013	0.0015	0.15

Notes:

- [1]. The consolidation parameters of Fill in the Outboard Area near the West Wall were assumed to be the same as the those near the East Wall.
- [2]. The  $C_{ce}$  value of SOLW corresponds to the low stress range and takes into account the effect of overconsolidation. This was discussed in the RA-D Cap Settlement Report.
- [3]. As mentioned in this report, the SOLW, Marl, and Silt and Clay layers were assumed as one layer for the purpose of calculating the time needed to reach 90% primary consolidation because the  $c_v$  values for these three layers are similar and much smaller than that of the Fill layer. In the Outboard Area near the West Wall, the  $c_v$  value of SOLW was applied to the combined layer. In the Outboard Area near the East Wall, the  $c_v$  value of Marl was applied to the combined layer.

# FIGURES




Figure 1. WB-B/HB Outboard Area Plan




Figure 2. Settlement Calculation Results for the 30-Year Period






Figure 2. Settlement Calculation Results for the 30-Year Period (continued)





Figure 3. Settlement Calculation Results for the 2-Year Period (Subarea 7 Only)

# ATTACHMENT A


## SUBSURFACE LAYER THICKNESS CONTOURS (WB-B/HB OUTBOARD AREA)




**Figure A-1. Thickness of Fill in WB-B/HB Outboard Area**

**Note:**


1. The subsurface thickness contours were developed based on the elevations of each layer interpreted from the available boring logs. This note applies to all the other figures included in this attachment.



**Figure A-2. Thickness of SOLW in WB-B/HB Outboard Area**



**Figure A-3. Thickness of Marl in WB-B/HB Outboard Area**



**Figure A-4. Thickness of Silt and Clay in WB-B/HB Outboard Area**

Note:

1. Thickness of Silt and Clay was estimated based on a limited number of deep borings that penetrated the Silt and Clay layer.

ATTACHMENT B

INTERPRETATION OF CONSOLIDATION  
PARAMETERS OF SUBSURFACE  
MATERIALS  
(WB-B/HB OUTBOARD AREA)



This attachment presents the interpretation of the consolidation parameters that were used for the cap-induced settlement calculations for the WB-B/HB outboard area near the West and East Walls. The consolidation parameters include the modified compression index ( $C_{ce}$ ), modified recompression index ( $C_{re}$ ), modified secondary compression index ( $C_{\alpha e}$ ), and coefficient of consolidation ( $C_v$ ). These parameters were interpreted from the available laboratory consolidation test data.

The interpreted values for  $C_{ce}$  and  $C_{re}$  of SOLW, Marl, and Silt and Clay are presented in Tables B-1 through B-6. The recommended consolidation parameters (i.e., mean values) are summarized in Table B-7. The interpretation of  $C_{\alpha e}$  and  $C_v$  for SOLW, Marl, and Silt and Clay are presented in Figures B-1 through B-12. The selected representative values shown on these figures were used for the settlement calculations.

Table B-1.  $C_{ce}$  and  $C_{re}$  for SOLW in Outboard Area near West Wall

Sample Location ID	Depth (ft)	Initial Void Ratio $e_0$	$C_c^{[2]}$	$C_r$	$C_{ce}^{[1,2]}$	$C_{re}^{[1]}$
HB-SB-02	10-12	3.16	0.04	0.01	0.010	0.002
HB-SB-18	10-12	1.72	0.18	0.01	0.065	0.004
HB-SB-126	5-7	3.07	0.21	0.02	0.051	0.004
HB-SB-143	22-24	3.73	0.20	0.01	0.043	0.002
Mean Value					0.042	0.003
Maximum Value					0.065	0.004
Minimum Value					0.010	0.002
Standard Deviation					0.023	0.001
Mean plus Standard Deviation					0.066	0.004
Mean minus Standard Deviation					0.019	0.002

Notes:

- [1].  $C_{ce}$  and  $C_{re}$  are modified compression index and recompression index, respectively. They are calculated as follows:  $C_{ce} = C_c / (1+e_0)$  and  $C_{re} = C_r / (1+e_0)$ . This note also applies to Tables B-2 through B-6.
- [2].  $C_c$  and  $C_{ce}$  values of SOLW correspond to the low stress range, as discussed in the RA-D Cap Settlement Report.

Table B-2.  $C_{ce}$  and  $C_{re}$  for Marl in Outboard Area near West Wall

Sample Location ID	Depth (ft)	Initial Void Ratio $e_0$	$C_c$	$C_r$	$C_{ce}$	$C_{re}$
HB-SB-01	20-22	1.62	0.31	0.01	0.118	0.004
HB-SB-15	24-26	1.57	0.33	0.04	0.129	0.016
HB-SB-126	36-38	2.56	0.83	0.02	0.233	0.006
HB-SB-143	42-44	1.08	0.27	0.03	0.129	0.015
Mean Value					0.152	0.010
Maximum Value					0.233	0.016
Minimum Value					0.118	0.004
Standard Deviation					0.054	0.006
Mean plus Standard Deviation					0.206	0.016
Mean minus Standard Deviation					0.098	0.004

Table B-3.  $C_{ce}$  and  $C_{re}$  for Silt and Clay in Outboard Area near West Wall

Sample Location ID	Depth (ft)	Initial Void Ratio $e_0$	$C_c$	$C_r$	$C_{ce}$	$C_{re}$
HB-SB-09	38-40	0.58	0.07	0.01	0.044	0.006
HB-SB-15	40-42	0.87	0.15	0.01	0.080	0.005
HB-SB-01	44-46	0.89	0.28	0.03	0.148	0.016
HB-SB-27	54-56	1.29	0.26	0.02	0.114	0.009
HB-SB-25	62-64	1.20	0.47	0.03	0.214	0.014
HB-SB-126	48-50	0.84	0.18	0.04	0.101	0.019
HB-SB-143	64-66	0.92	0.22	0.05	0.116	0.024
Mean Value					0.117	0.013
Maximum Value					0.214	0.024
Minimum Value					0.044	0.005
Standard Deviation					0.054	0.007
Mean plus Standard Deviation					0.170	0.020
Mean minus Standard Deviation					0.063	0.006

Table B-4.  $C_{ce}$  and  $C_{re}$  for Fill in Outboard Area near East Wall

Sample Location ID	Depth (ft)	Initial Void Ratio $e_0$	$C_c$	$C_r$	$C_{ce}$	$C_{re}$
HB-SB-202	5-7	0.86	0.11	0.01	0.061	0.006
Mean Value					0.061	0.006

Table B-5.  $C_{ce}$  and  $C_{re}$  for Marl in Outboard Area near East Wall

Sample Location ID	Depth (ft)	Initial Void Ratio $e_0$	$C_c$	$C_r$	$C_{ce}$	$C_{re}$
HB-SB-209	34-36	1.61	0.51	0.05	0.194	0.020
HB-SB-97	24-26	2.38	0.76	0.04	0.224	0.013
HB-SB-102	40-42	1.56	0.38	0.03	0.150	0.011
HB-SB-107	14-16	2.56	0.71	0.01	0.199	0.004
HB-SB-20	22-24	1.54	0.29	0.01	0.114	0.004
Mean Value					0.176	0.010
Maximum Value					0.224	0.020
Minimum Value					0.114	0.004
Standard Deviation					0.044	0.007
Mean plus Standard Deviation					0.220	0.017
Mean minus Standard Deviation					0.132	0.004

Table B-6.  $C_{ce}$  and  $C_{re}$  for Silt and Clay in Outboard Area near East Wall

Sample Location ID	Depth (ft)	Initial Void Ratio $e_0$	$C_c$	$C_r$	$C_{ce}$	$C_{re}$
HB-SB-97	60-62	0.74	0.11	0.01	0.066	0.008
HB-SB-102	54-56	2.14	0.57	0.05	0.183	0.017
HB-SB-104	76-78	0.94	0.27	0.03	0.138	0.015
Mean Value					0.129	0.013
Maximum Value					0.183	0.017
Minimum Value					0.066	0.008
Standard Deviation					0.059	0.004
Mean plus Standard Deviation					0.188	0.018
Mean minus Standard Deviation					0.070	0.009

Table B-7. Summary of Recommended Consolidation Parameters for Settlement Calculations

Area	Material	Recommended Consolidation Parameters			
		$C_{\text{ce}}$	$C_{\text{re}}$	$C_{\text{ae}}$	$c_v$ (ft <sup>2</sup> /d)
Outboard Area near West Wall	SOLW	0.042 <sup>[1]</sup>	0.003	0.0006	0.60
	Marl	0.152	0.010	0.0008	0.50
	Silt and Clay	0.117	0.013	0.0015	0.15
Outboard Area near East Wall	Fill	0.061	0.006	0.0003	4.50
	Marl	0.176	0.010	0.0030	0.25
	Silt and Clay	0.129	0.013	0.0015	0.15

Note:

1. The  $C_{\text{ce}}$  value of SOLW corresponds to the low stress range, as discussed in the RA-D Cap Settlement Report..






Figure B-1. Interpretation of Modified Secondary Compression Index for SOLW  
(Outboard Area near West Wall)

Note:

The ratio of  $\sigma_v'/\sigma_p'$  of SOLW in the field before and after capping was estimated to be between 0.1 and 1 according to the assumed subsurface layer thicknesses.




Figure B-2. Interpretation of Coefficient of Consolidation for SOLW  
(Outboard Area near West Wall)

Note:

The ratio of  $\sigma_v'/\sigma_p'$  of SOLW in the field before and after capping was estimated to be between 0.1 and 1 according to the assumed subsurface layer thicknesses.




Figure B-3. Interpretation of Modified Secondary Compression Index for Marl  
(Outboard Area near West Wall)

Note:

The ratio of  $\sigma_v'/\sigma_p'$  of Marl in the field before and after capping was estimated to be between 0.1 and 3 according to the assumed subsurface layer thicknesses.




Figure B-4. Interpretation of Coefficient of Consolidation for Marl  
(Outboard Area near West Wall)

Note:

The ratio of  $\sigma_v'/\sigma_p'$  of Marl in the field before and after capping was estimated to be between 0.1 and 3 according to the assumed subsurface layer thicknesses.




Figure B-5. Interpretation of Modified Secondary Compression Index for Silt and Clay  
(Outboard Area near West Wall)

Note:

The ratio of  $\sigma_v'/\sigma_p'$  of Silt and Clay in the field before and after capping was estimated to be between 0.4 and 2 according to the assumed subsurface layer thicknesses.




Figure B-6. Interpretation of Coefficient of Consolidation for Silt and Clay  
(Outboard Area near West Wall)

Note:

The ratio of  $\sigma_v'/\sigma_p'$  of Silt and Clay in the field before and after capping was estimated to be between 0.4 and 2 according to the assumed subsurface layer thicknesses.




Figure B-7. Interpretation of Modified Secondary Compression Index for Fill  
(Outboard Area near East Wall)

Note:

The ratio of  $\sigma_v'/\sigma_p'$  of Fill in the field before and after capping was estimated to be between 0.1 and 2 according to the assumed subsurface layer thicknesses.




Figure B-8. Interpretation of Coefficient of Consolidation for Fill  
(Outboard Area near East Wall)

Note:

The ratio of  $\sigma_v'/\sigma_p'$  of Fill in the field before and after capping was estimated to be between 0.1 and 2 according to the assumed subsurface layer thicknesses.






Figure B-9. Interpretation of Modified Secondary Compression Index for Marl  
(Outboard Area near East Wall)

Note:

The ratio of  $\sigma_v'/\sigma_p'$  of Marl in the field before and after capping was estimated to be between 0.1 and 3 according to the assumed subsurface layer thicknesses.




Figure B-10. Interpretation of Coefficient of Consolidation for Marl  
(Outboard Area near East Wall)

Note:

The ratio of  $\sigma_v'/\sigma_p'$  of Marl in the field before and after capping was estimated to be between 0.1 and 3 according to the assumed subsurface layer thicknesses.




Figure B-11. Interpretation of Modified Secondary Compression Index for Silt and Clay  
(Outboard Area near East Wall)

Note:

The ratio of  $\sigma_v'/\sigma_p'$  of Silt and Clay in the field before and after capping was estimated to be between 0.4 and 3 according to the assumed subsurface layer thicknesses.




Figure B-12. Interpretation of Coefficient of Consolidation for Silt and Clay  
(Outboard Area near East Wall)

Note:

The ratio of  $\sigma_v'/\sigma_p'$  of Silt and Clay in the field before and after capping was estimated to be between 0.4 and 3 according to the assumed subsurface layer thicknesses.

# ATTACHMENT C

## EXAMPLE SETTLEMENT CALCULATION

(For Subarea 7 with 3 ft removal and 4 ft thick cap)

## An Example of Settlement Calculation

Input:										
Removal Depth	3	ft								
Consider Total Settlement	30	years								
Groundwater Table	1	ft, bgs								
Soil Layers	Thickness (ft)	Unit Weight (pcf)	OCR	$C_{ce}$	$C_{re}$	$C_{\alpha}$	Coef. of Con. $c_v$ (ft <sup>2</sup> /d)	Time of 90% primary con. (years)	$t_2/t_1$ for Secondary Con.	# of Sublayers
Cap	4	120								
Fill	10	92	2	0.061	0.0060	0.0003	4.500	0.1	1185.9	4
SOLW	0	88	1	0.042	0.0030	0.0006	0.250	21.0	1.4	0
Marl	35	97	1.2	0.176	0.0100	0.0030	0.250	21.0	1.4	14
Silt/Clay	60	111	1	0.129	0.0130	0.0015	0.250	21.0	1.4	12
Water		62.4								
Note: 1. Assume secondary consolidation starts at the time when 90% of primary consolidation have occurred.										
Calculated Settlement (ft):										
	Primary Settlement	Secondary Settlement	Total Settlement							
Fill	0.016	0.006	0.023							
SOLW	0.000	0.000	0.000							
Marl	0.194	0.015	0.210							
Silt/Clay	0.256	0.013	0.270							
Total	0.47	0.03	0.50	=	6.0 in					

Total Primary	0.016	Total Primary	0.000
Total Secondary	0.006	Total Secondary	0.000
Total	0.023	Total	0.000
Calculation for Fill		Calculation for SOLW	
Layer No.	1	Layer No.	1
Layer Thickness, m / ft	1.75	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	0.875	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	5E-11
Midpoint Depth from Ori Ground Surface, m/ft	3.875	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	177.1	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	25.9	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	131.5	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	354.2	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{ce}$	0.061	Modified Primary Compression Index, $C_{ce}$	0.042
Modified Recompression Index, $C_{re}$	0.006	Modified Recompression Index, $C_{re}$	0.003
Modified Secondary Compression Index, $C_{\alpha e}$	0.0003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0006
ratio of $t_2 / t_1$	1185.9	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.007	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.002	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.009	Total Settlement (m / ft)	0.000
Layer No.	2	Layer No.	2
Layer Thickness, m / ft	1.75	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	2.625	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	1.5E-10
Midpoint Depth from Ori Ground Surface, m/ft	5.625	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	228.9	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	77.7	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	183.3	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	457.8	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{ce}$	0.061	Modified Primary Compression Index, $C_{ce}$	0.042
Modified Recompression Index, $C_{re}$	0.006	Modified Recompression Index, $C_{re}$	0.003
Modified Secondary Compression Index, $C_{\alpha e}$	0.0003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0006
ratio of $t_2 / t_1$	1185.9	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.004	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.002	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.006	Total Settlement (m / ft)	0.000
Layer No.	3	Layer No.	3
Layer Thickness, m / ft	1.75	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	4.375	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	2.5E-10
Midpoint Depth from Ori Ground Surface, m/ft	7.375	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	280.7	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	129.5	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	235.1	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	561.4	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{ce}$	0.061	Modified Primary Compression Index, $C_{ce}$	0.042
Modified Recompression Index, $C_{re}$	0.006	Modified Recompression Index, $C_{re}$	0.003
Modified Secondary Compression Index, $C_{\alpha e}$	0.0003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0006
ratio of $t_2 / t_1$	1185.9	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.003	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.002	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.004	Total Settlement (m / ft)	0.000

Layer No. 4		Layer No. 4	
Layer Thickness, m / ft	1.75	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	6.125	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	3.5E-10
Midpoint Depth from Ori Ground Surface, m/ft	9.125	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	332.5	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	181.3	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	286.9	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	665	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{ce}$	0.061	Modified Primary Compression Index, $C_{ce}$	0.042
Modified Recompression Index, $C_{re}$	0.006	Modified Recompression Index, $C_{re}$	0.003
Modified Secondary Compression Index, $C_{ae}$	0.0003	Modified Secondary Compression Index, $C_{ae}$	0.0006
ratio of $t_2 / t_1$	1185.9	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.002	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.002	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.004	Total Settlement (m / ft)	0.000
Layer No. 5		Layer No. 5	
Layer Thickness, m / ft	1E-10	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	4.5E-10	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	4.5E-10
Midpoint Depth from Ori Ground Surface, m/ft	3	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	151.2	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	1.332E-08	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	105.6	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	302.4	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{ce}$	0.061	Modified Primary Compression Index, $C_{ce}$	0.042
Modified Recompression Index, $C_{re}$	0.006	Modified Recompression Index, $C_{re}$	0.003
Modified Secondary Compression Index, $C_{ae}$	0.0003	Modified Secondary Compression Index, $C_{ae}$	0.0006
ratio of $t_2 / t_1$	1185.9	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.000	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.000	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.000	Total Settlement (m / ft)	0.000
Layer No. 6		Layer No. 6	
Layer Thickness, m / ft	1E-10	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	5.5E-10	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	5.5E-10
Midpoint Depth from Ori Ground Surface, m/ft	3	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	151.2	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	1.628E-08	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	105.6	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	302.4	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{ce}$	0.061	Modified Primary Compression Index, $C_{ce}$	0.042
Modified Recompression Index, $C_{re}$	0.006	Modified Recompression Index, $C_{re}$	0.003
Modified Secondary Compression Index, $C_{ae}$	0.0003	Modified Secondary Compression Index, $C_{ae}$	0.0006
ratio of $t_2 / t_1$	1185.9	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.000	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.000	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.000	Total Settlement (m / ft)	0.000



Layer No. 7		Layer No. 7	
Layer Thickness, m / ft	1E-10	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	6.5E-10	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	6.5E-10
Midpoint Depth from Ori Ground Surface, m/ft	3	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	151.2	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	1.924E-08	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	105.6	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	302.4	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{ce}$	0.061	Modified Primary Compression Index, $C_{ce}$	0.042
Modified Recompression Index, $C_{re}$	0.006	Modified Recompression Index, $C_{re}$	0.003
Modified Secondary Compression Index, $C_{\alpha e}$	0.0003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0006
ratio of t2 / t1	1185.9	ratio of t2 / t1	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.000	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.000	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.000	Total Settlement (m / ft)	0.000
Layer No. 8		Layer No. 8	
Layer Thickness, m / ft	1E-10	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	7.5E-10	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	7.5E-10
Midpoint Depth from Ori Ground Surface, m/ft	3	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	151.2	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	2.22E-08	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	105.6	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	302.4	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{ce}$	0.061	Modified Primary Compression Index, $C_{ce}$	0.042
Modified Recompression Index, $C_{re}$	0.006	Modified Recompression Index, $C_{re}$	0.003
Modified Secondary Compression Index, $C_{\alpha e}$	0.0003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0006
ratio of t2 / t1	1185.9	ratio of t2 / t1	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.000	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.000	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.000	Total Settlement (m / ft)	0.000
Layer No. 9		Layer No. 9	
Layer Thickness, m / ft	1E-10	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	8.5E-10	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	8.5E-10
Midpoint Depth from Ori Ground Surface, m/ft	3	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	151.2	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	2.516E-08	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	105.6	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	302.4	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{ce}$	0.061	Modified Primary Compression Index, $C_{ce}$	0.042
Modified Recompression Index, $C_{re}$	0.006	Modified Recompression Index, $C_{re}$	0.003
Modified Secondary Compression Index, $C_{\alpha e}$	0.0003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0006
ratio of t2 / t1	1185.9	ratio of t2 / t1	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.000	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.000	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.000	Total Settlement (m / ft)	0.000

Layer No. 10		Layer No. 10	
Layer Thickness, m / ft	1E-10	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	9.5E-10	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	9.5E-10
Midpoint Depth from Ori Ground Surface, m/ft	3	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	151.2	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	2.812E-08	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	105.6	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	302.4	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{c\epsilon}$	0.061	Modified Primary Compression Index, $C_{c\epsilon}$	0.042
Modified Recompression Index, $C_{r\epsilon}$	0.006	Modified Recompression Index, $C_{r\epsilon}$	0.003
Modified Secondary Compression Index, $C_{\alpha\epsilon}$	0.0003	Modified Secondary Compression Index, $C_{\alpha\epsilon}$	0.0006
ratio of $t_2 / t_1$	1185.9	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.000	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.000	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.000	Total Settlement (m / ft)	0.000
Layer No. 11		Layer No. 11	
Layer Thickness, m / ft	1E-10	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	1.05E-09	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	1.05E-09
Midpoint Depth from Ori Ground Surface, m/ft	3	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	151.2	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	3.108E-08	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	105.6	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	302.4	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{c\epsilon}$	0.061	Modified Primary Compression Index, $C_{c\epsilon}$	0.042
Modified Recompression Index, $C_{r\epsilon}$	0.006	Modified Recompression Index, $C_{r\epsilon}$	0.003
Modified Secondary Compression Index, $C_{\alpha\epsilon}$	0.0003	Modified Secondary Compression Index, $C_{\alpha\epsilon}$	0.0006
ratio of $t_2 / t_1$	1185.9	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.000	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.000	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.000	Total Settlement (m / ft)	0.000
Layer No. 12		Layer No. 12	
Layer Thickness, m / ft	1E-10	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	1.15E-09	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	1.15E-09
Midpoint Depth from Ori Ground Surface, m/ft	3	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	151.2	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	3.404E-08	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	105.6	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	302.4	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{c\epsilon}$	0.061	Modified Primary Compression Index, $C_{c\epsilon}$	0.042
Modified Recompression Index, $C_{r\epsilon}$	0.006	Modified Recompression Index, $C_{r\epsilon}$	0.003
Modified Secondary Compression Index, $C_{\alpha\epsilon}$	0.0003	Modified Secondary Compression Index, $C_{\alpha\epsilon}$	0.0006
ratio of $t_2 / t_1$	1185.9	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.000	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.000	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.000	Total Settlement (m / ft)	0.000

Layer No. 13		Layer No. 13	
Layer Thickness, m / ft	1E-10	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	1.25E-09	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	1.25E-09
Midpoint Depth from Ori Ground Surface, m/ft	3	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	151.2	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	3.7E-08	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	105.6	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	302.4	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{c\epsilon}$	0.061	Modified Primary Compression Index, $C_{c\epsilon}$	0.042
Modified Recompression Index, $C_{r\epsilon}$	0.006	Modified Recompression Index, $C_{r\epsilon}$	0.003
Modified Secondary Compression Index, $C_{\alpha\epsilon}$	0.0003	Modified Secondary Compression Index, $C_{\alpha\epsilon}$	0.0006
ratio of $t_2 / t_1$	1185.9	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.000	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.000	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.000	Total Settlement (m / ft)	0.000
Layer No. 14		Layer No. 14	
Layer Thickness, m / ft	1E-10	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	1.35E-09	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	1.35E-09
Midpoint Depth from Ori Ground Surface, m/ft	3	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	151.2	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	3.996E-08	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	105.6	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	302.4	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{c\epsilon}$	0.061	Modified Primary Compression Index, $C_{c\epsilon}$	0.042
Modified Recompression Index, $C_{r\epsilon}$	0.006	Modified Recompression Index, $C_{r\epsilon}$	0.003
Modified Secondary Compression Index, $C_{\alpha\epsilon}$	0.0003	Modified Secondary Compression Index, $C_{\alpha\epsilon}$	0.0006
ratio of $t_2 / t_1$	1185.9	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.000	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.000	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.000	Total Settlement (m / ft)	0.000
Layer No. 15		Layer No. 15	
Layer Thickness, m / ft	1E-10	Layer Thickness, m / ft	1E-10
Midpoint Depth from Removal Bot, m/ft	1.45E-09	Midpoint Depth from T. of SLOW/Removal Bot, m/ft	1.45E-09
Midpoint Depth from Ori Ground Surface, m/ft	3	Midpoint Depth from Ori Ground Surface, m/ft	10
Effective Stress Before Removal, KPa/psf	151.2	Effective Stress Before Removal, KPa/psf	358.4
Initial Effective Stress, KPa/psf	4.292E-08	Initial Effective Stress, KPa/psf	207.2
Final Effective Stress, KPa/psf	105.6	Final Effective Stress, KPa/psf	562.4
OCR	2	OCR	1
Preconsolidation Pressure, KPa/psf	302.4	Preconsolidation Pressure, KPa/psf	358.4
Modified Primary Compression Index, $C_{c\epsilon}$	0.061	Modified Primary Compression Index, $C_{c\epsilon}$	0.042
Modified Recompression Index, $C_{r\epsilon}$	0.006	Modified Recompression Index, $C_{r\epsilon}$	0.003
Modified Secondary Compression Index, $C_{\alpha\epsilon}$	0.0003	Modified Secondary Compression Index, $C_{\alpha\epsilon}$	0.0006
ratio of $t_2 / t_1$	1185.9	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.000	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.000	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.000	Total Settlement (m / ft)	0.000

Total Primary	0.194	Total Primary	0.256
Total Secondary	0.015	Total Secondary	0.013
Total	0.210	Total	0.270
Calculation for Marl		Calculation for Silt and Clay	
Layer No.	1	Layer No.	1
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	5
Midpoint Depth from T. of Marl/Removal Bot, m/f	1.25	Midpoint Depth from T. of Silt/Clay, m/ft	2.5
Midpoint Depth from Ori Ground Surface, m/ft	11.25	Midpoint Depth from Ori Ground Surface, m/ft	47.5
Effective Stress Before Removal, KPa/psf	401.65	Effective Stress Before Removal, KPa/psf	1690.9
Initial Effective Stress, KPa/psf	250.45	Initial Effective Stress, KPa/psf	1539.7
Final Effective Stress, KPa/psf	605.65	Final Effective Stress, KPa/psf	1894.9
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	481.98	Preconsolidation Pressure, KPa/psf	1690.9
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{ae}$	0.003	Modified Secondary Compression Index, $C_{ae}$	0.0015
ratio of $t_2 / t_1$	1.4	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.051	Primary Settlement, (m / ft)	0.035
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.001
Total Settlement (m / ft)	0.052	Total Settlement (m / ft)	0.036
Layer No.		Layer No.	
2		2	
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	5
Midpoint Depth from T. of Marl/Removal Bot, m/f	3.75	Midpoint Depth from T. of Silt/Clay, m/ft	7.5
Midpoint Depth from Ori Ground Surface, m/ft	13.75	Midpoint Depth from Ori Ground Surface, m/ft	52.5
Effective Stress Before Removal, KPa/psf	488.15	Effective Stress Before Removal, KPa/psf	1933.9
Initial Effective Stress, KPa/psf	336.95	Initial Effective Stress, KPa/psf	1782.7
Final Effective Stress, KPa/psf	692.15	Final Effective Stress, KPa/psf	2137.9
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	585.78	Preconsolidation Pressure, KPa/psf	1933.9
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{ae}$	0.003	Modified Secondary Compression Index, $C_{ae}$	0.0015
ratio of $t_2 / t_1$	1.4	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.038	Primary Settlement, (m / ft)	0.030
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.001
Total Settlement (m / ft)	0.039	Total Settlement (m / ft)	0.031
Layer No.		Layer No.	
3		3	
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	5
Midpoint Depth from T. of Marl/Removal Bot, m/f	6.25	Midpoint Depth from T. of Silt/Clay, m/ft	12.5
Midpoint Depth from Ori Ground Surface, m/ft	16.25	Midpoint Depth from Ori Ground Surface, m/ft	57.5
Effective Stress Before Removal, KPa/psf	574.65	Effective Stress Before Removal, KPa/psf	2176.9
Initial Effective Stress, KPa/psf	423.45	Initial Effective Stress, KPa/psf	2025.7
Final Effective Stress, KPa/psf	778.65	Final Effective Stress, KPa/psf	2380.9
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	689.58	Preconsolidation Pressure, KPa/psf	2176.9
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{ae}$	0.003	Modified Secondary Compression Index, $C_{ae}$	0.0015
ratio of $t_2 / t_1$	1.4	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.029	Primary Settlement, (m / ft)	0.027
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.001
Total Settlement (m / ft)	0.030	Total Settlement (m / ft)	0.028

<b>Layer No. 4</b>		<b>Layer No. 4</b>	
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	5
Midpoint Depth from T. of Marl/Removal Bot, m/f	8.75	Midpoint Depth from T. of Silt/Clay, m/ft	17.5
Midpoint Depth from Ori Ground Surface, m/ft	18.75	Midpoint Depth from Ori Ground Surface, m/ft	62.5
Effective Stress Before Removal, KPa/psf	661.15	Effective Stress Before Removal, KPa/psf	2419.9
Initial Effective Stress, KPa/psf	509.95	Initial Effective Stress, KPa/psf	2268.7
Final Effective Stress, KPa/psf	865.15	Final Effective Stress, KPa/psf	2623.9
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	793.38	Preconsolidation Pressure, KPa/psf	2419.9
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{\alpha e}$	0.003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0015
ratio of $t_2 / t_1$	1.4	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.021	Primary Settlement, (m / ft)	0.024
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.001
Total Settlement (m / ft)	0.022	Total Settlement (m / ft)	0.026
<b>Layer No. 5</b>		<b>Layer No. 5</b>	
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	5
Midpoint Depth from T. of Marl/Removal Bot, m/f	11.25	Midpoint Depth from T. of Silt/Clay, m/ft	22.5
Midpoint Depth from Ori Ground Surface, m/ft	21.25	Midpoint Depth from Ori Ground Surface, m/ft	67.5
Effective Stress Before Removal, KPa/psf	747.65	Effective Stress Before Removal, KPa/psf	2662.9
Initial Effective Stress, KPa/psf	596.45	Initial Effective Stress, KPa/psf	2511.7
Final Effective Stress, KPa/psf	951.65	Final Effective Stress, KPa/psf	2866.9
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	897.18	Preconsolidation Pressure, KPa/psf	2662.9
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{\alpha e}$	0.003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0015
ratio of $t_2 / t_1$	1.4	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.016	Primary Settlement, (m / ft)	0.022
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.001
Total Settlement (m / ft)	0.017	Total Settlement (m / ft)	0.023
<b>Layer No. 6</b>		<b>Layer No. 6</b>	
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	5
Midpoint Depth from T. of Marl/Removal Bot, m/f	13.75	Midpoint Depth from T. of Silt/Clay, m/ft	27.5
Midpoint Depth from Ori Ground Surface, m/ft	23.75	Midpoint Depth from Ori Ground Surface, m/ft	72.5
Effective Stress Before Removal, KPa/psf	834.15	Effective Stress Before Removal, KPa/psf	2905.9
Initial Effective Stress, KPa/psf	682.95	Initial Effective Stress, KPa/psf	2754.7
Final Effective Stress, KPa/psf	1038.15	Final Effective Stress, KPa/psf	3109.9
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	1000.98	Preconsolidation Pressure, KPa/psf	2905.9
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{\alpha e}$	0.003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0015
ratio of $t_2 / t_1$	1.4	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.011	Primary Settlement, (m / ft)	0.021
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.001
Total Settlement (m / ft)	0.012	Total Settlement (m / ft)	0.022

<b>Layer No. 7</b>		<b>Layer No. 7</b>	
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	5
Midpoint Depth from T. of Marl/Removal Bot, m/f	16.25	Midpoint Depth from T. of Silt/Clay, m/ft	32.5
Midpoint Depth from Ori Ground Surface, m/ft	26.25	Midpoint Depth from Ori Ground Surface, m/ft	77.5
Effective Stress Before Removal, KPa/psf	920.65	Effective Stress Before Removal, KPa/psf	3148.9
Initial Effective Stress, KPa/psf	769.45	Initial Effective Stress, KPa/psf	2997.7
Final Effective Stress, KPa/psf	1124.65	Final Effective Stress, KPa/psf	3352.9
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	1104.78	Preconsolidation Pressure, KPa/psf	3148.9
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{\alpha e}$	0.003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0015
ratio of $t_2 / t_1$	1.4	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.007	Primary Settlement, (m / ft)	0.019
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.001
Total Settlement (m / ft)	0.008	Total Settlement (m / ft)	0.020
<b>Layer No. 8</b>		<b>Layer No. 8</b>	
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	5
Midpoint Depth from T. of Marl/Removal Bot, m/f	18.75	Midpoint Depth from T. of Silt/Clay, m/ft	37.5
Midpoint Depth from Ori Ground Surface, m/ft	28.75	Midpoint Depth from Ori Ground Surface, m/ft	82.5
Effective Stress Before Removal, KPa/psf	1007.15	Effective Stress Before Removal, KPa/psf	3391.9
Initial Effective Stress, KPa/psf	855.95	Initial Effective Stress, KPa/psf	3240.7
Final Effective Stress, KPa/psf	1211.15	Final Effective Stress, KPa/psf	3595.9
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	1208.58	Preconsolidation Pressure, KPa/psf	3391.9
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{\alpha e}$	0.003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0015
ratio of $t_2 / t_1$	1.4	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.004	Primary Settlement, (m / ft)	0.018
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.001
Total Settlement (m / ft)	0.005	Total Settlement (m / ft)	0.019
<b>Layer No. 9</b>		<b>Layer No. 9</b>	
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	5
Midpoint Depth from T. of Marl/Removal Bot, m/f	21.25	Midpoint Depth from T. of Silt/Clay, m/ft	42.5
Midpoint Depth from Ori Ground Surface, m/ft	31.25	Midpoint Depth from Ori Ground Surface, m/ft	87.5
Effective Stress Before Removal, KPa/psf	1093.65	Effective Stress Before Removal, KPa/psf	3634.9
Initial Effective Stress, KPa/psf	942.45	Initial Effective Stress, KPa/psf	3483.7
Final Effective Stress, KPa/psf	1297.65	Final Effective Stress, KPa/psf	3838.9
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	1312.38	Preconsolidation Pressure, KPa/psf	3634.9
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{\alpha e}$	0.003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0015
ratio of $t_2 / t_1$	1.4	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.003	Primary Settlement, (m / ft)	0.016
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.001
Total Settlement (m / ft)	0.005	Total Settlement (m / ft)	0.018

<b>Layer No. 10</b>		<b>Layer No. 10</b>	
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	5
Midpoint Depth from T. of Marl/Removal Bot, m/f	23.75	Midpoint Depth from T. of Silt/Clay, m/ft	47.5
Midpoint Depth from Ori Ground Surface, m/ft	33.75	Midpoint Depth from Ori Ground Surface, m/ft	92.5
Effective Stress Before Removal, KPa/psf	1180.15	Effective Stress Before Removal, KPa/psf	3877.9
Initial Effective Stress, KPa/psf	1028.95	Initial Effective Stress, KPa/psf	3726.7
Final Effective Stress, KPa/psf	1384.15	Final Effective Stress, KPa/psf	4081.9
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	1416.18	Preconsolidation Pressure, KPa/psf	3877.9
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{\alpha e}$	0.003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0015
ratio of $t_2 / t_1$	1.4	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.003	Primary Settlement, (m / ft)	0.015
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.001
Total Settlement (m / ft)	0.004	Total Settlement (m / ft)	0.017
<b>Layer No. 11</b>		<b>Layer No. 11</b>	
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	5
Midpoint Depth from T. of Marl/Removal Bot, m/f	26.25	Midpoint Depth from T. of Silt/Clay, m/ft	52.5
Midpoint Depth from Ori Ground Surface, m/ft	36.25	Midpoint Depth from Ori Ground Surface, m/ft	97.5
Effective Stress Before Removal, KPa/psf	1266.65	Effective Stress Before Removal, KPa/psf	4120.9
Initial Effective Stress, KPa/psf	1115.45	Initial Effective Stress, KPa/psf	3969.7
Final Effective Stress, KPa/psf	1470.65	Final Effective Stress, KPa/psf	4324.9
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	1519.98	Preconsolidation Pressure, KPa/psf	4120.9
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{\alpha e}$	0.003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0015
ratio of $t_2 / t_1$	1.4	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.003	Primary Settlement, (m / ft)	0.015
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.001
Total Settlement (m / ft)	0.004	Total Settlement (m / ft)	0.016
<b>Layer No. 12</b>		<b>Layer No. 12</b>	
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	5
Midpoint Depth from T. of Marl/Removal Bot, m/f	28.75	Midpoint Depth from T. of Silt/Clay, m/ft	57.5
Midpoint Depth from Ori Ground Surface, m/ft	38.75	Midpoint Depth from Ori Ground Surface, m/ft	102.5
Effective Stress Before Removal, KPa/psf	1353.15	Effective Stress Before Removal, KPa/psf	4363.9
Initial Effective Stress, KPa/psf	1201.95	Initial Effective Stress, KPa/psf	4212.7
Final Effective Stress, KPa/psf	1557.15	Final Effective Stress, KPa/psf	4567.9
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	1623.78	Preconsolidation Pressure, KPa/psf	4363.9
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{\alpha e}$	0.003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0015
ratio of $t_2 / t_1$	1.4	ratio of $t_2 / t_1$	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.003	Primary Settlement, (m / ft)	0.014
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.001
Total Settlement (m / ft)	0.004	Total Settlement (m / ft)	0.015



Layer No. 13		Layer No. 13	
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	1E-10
Midpoint Depth from T. of Marl/Removal Bot, m/f	31.25	Midpoint Depth from T. of Silt/Clay, m/ft	1.25E-09
Midpoint Depth from Ori Ground Surface, m/ft	41.25	Midpoint Depth from Ori Ground Surface, m/ft	45
Effective Stress Before Removal, KPa/psf	1439.65	Effective Stress Before Removal, KPa/psf	1569.4
Initial Effective Stress, KPa/psf	1288.45	Initial Effective Stress, KPa/psf	1418.2
Final Effective Stress, KPa/psf	1643.65	Final Effective Stress, KPa/psf	1773.4
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	1727.58	Preconsolidation Pressure, KPa/psf	1569.4
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{\alpha e}$	0.003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0015
ratio of t2 / t1	1.4	ratio of t2 / t1	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.003	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.004	Total Settlement (m / ft)	0.000
Layer No. 14		Layer No. 14	
Layer Thickness, m / ft	2.5	Layer Thickness, m / ft	1E-10
Midpoint Depth from T. of Marl/Removal Bot, m/f	33.75	Midpoint Depth from T. of Silt/Clay, m/ft	1.35E-09
Midpoint Depth from Ori Ground Surface, m/ft	43.75	Midpoint Depth from Ori Ground Surface, m/ft	45
Effective Stress Before Removal, KPa/psf	1526.15	Effective Stress Before Removal, KPa/psf	1569.4
Initial Effective Stress, KPa/psf	1374.95	Initial Effective Stress, KPa/psf	1418.2
Final Effective Stress, KPa/psf	1730.15	Final Effective Stress, KPa/psf	1773.4
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	1831.38	Preconsolidation Pressure, KPa/psf	1569.4
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{\alpha e}$	0.003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0015
ratio of t2 / t1	1.4	ratio of t2 / t1	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.002	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.001	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.004	Total Settlement (m / ft)	0.000
Layer No. 15		Layer No. 15	
Layer Thickness, m / ft	1E-10	Layer Thickness, m / ft	1E-10
Midpoint Depth from T. of Marl/Removal Bot, m/f	1.45E-09	Midpoint Depth from T. of Silt/Clay, m/ft	1.45E-09
Midpoint Depth from Ori Ground Surface, m/ft	10	Midpoint Depth from Ori Ground Surface, m/ft	45
Effective Stress Before Removal, KPa/psf	358.4	Effective Stress Before Removal, KPa/psf	1569.4
Initial Effective Stress, KPa/psf	207.2	Initial Effective Stress, KPa/psf	1418.2
Final Effective Stress, KPa/psf	562.4	Final Effective Stress, KPa/psf	1773.4
OCR	1.2	OCR	1
Preconsolidation Pressure, KPa/psf	430.08	Preconsolidation Pressure, KPa/psf	1569.4
Modified Primary Compression Index, $C_{ce}$	0.176	Modified Primary Compression Index, $C_{ce}$	0.129
Modified Recompression Index, $C_{re}$	0.01	Modified Recompression Index, $C_{re}$	0.013
Modified Secondary Compression Index, $C_{\alpha e}$	0.003	Modified Secondary Compression Index, $C_{\alpha e}$	0.0015
ratio of t2 / t1	1.4	ratio of t2 / t1	1.4
Settlements		Settlements	
Primary Settlement, (m / ft)	0.000	Primary Settlement, (m / ft)	0.000
Secondary Settlement (m / ft)	0.000	Secondary Settlement (m / ft)	0.000
Total Settlement (m / ft)	0.000	Total Settlement (m / ft)	0.000